

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

ME-TEX SUPPLY COMPANY

Company or Operator

WALLACE - STATE

Lease

Well No. 4 in Lot 5 of Sec. 3, T. 21 S.

R. 36E, N. M. P. M., EUNICE Field, LEA County.

Well is 330 feet south of the North line and 330 feet west of the East line of LOT 5 - SEC. 3-21-36

If State land the oil and gas lease is No. A - 1375 Assignment No. 13

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is WALLACE ESTATE - G.C. CATRON - AGENT Address SANTA FE, NEW MEXICO

Drilling commenced JUNE 28 19 37 Drilling was completed JULY 25 19 37

Name of drilling contractor TWO STATES DRILLING COMPANY Address DALLAS, TEXAS

Elevation above sea level at top of casing 3530 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3715 to 3840 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 2, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
10"	50	8		149'	FLAT SHOE			
7 5/8"	32	8		1095'	"			
5 1/2"	20	10		2406'	"			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13"	10"	149'	250	HALLIBURTON		
9 5/4"	7 5/8"	1244'	200	"		
6 3/4"	5 1/2"	3650'	550	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
4 1/2"	BAKELITE	LIQUID GLY.	240 LBS.	7-26-37	3740 to 3840	3840
4 1/2"	BAKELITE	LIQUID GLY.	240 LBS.	8-5-37	3725 to 3840	3840

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3840 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing July 30 19 37

The production of the first 24 hours was 73 barrels of fluid of which 100 % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours 150 Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

H. C. PATRICK Driller G. H. MILLS Driller

V. E. BEASLEY Driller H. S. STOVALL Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 23

day of SEPTEMBER 19 37

G. C. Catron
Notary Public.

My Commission Expires January 14, 1940

My Commission expires

NOB 3, NEW MEXICO SEPT. 23, 1937

Name *W. A. Bussey*

Position AUDITOR

Representing ME-TEX SUPPLY COMPANY

Address MOES, NEW MEXICO

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	100		Shells and surface sand
100	139		Sand and shells
139	149		Red bed
149	224		" "
224	354		" "
354	428		Red bed and red rock
428	730		Red rock and red shale
730	830		Red rock and red bed
830	930		" " " " "
930	1000		" " " " "
1000	1050		" " " " "
1050	1094		" " " " "
1094	1202		Red rock, red shale and gyp
1202	1238		Red rock, red bed and gyp
1238	1254		Anhydrite
1254	1257		Anhydrite and red rock
1257	1350		Anhydrite
1350	1377		Salt and anhydrite
1377	1565		" " "
1565	1660		Anhydrite with streaks of salt
1660	1940		Salt
1940	2103		Salt and anhydrite
2103	2300		" " "
2300	2510		Salt
2510	2515		"
2515	2580		Anhydrite
2580	2650		"
2650	2714		"
2714	2756		Anhydrite and gyp
2756	2775		Anhydrite
2775	2828		"
2828	2874		Anhydrite and lime
2874	2920		Lime
2920	2960		"
2960	3002		"
3002	3038		"
3038	3084		"
3084	3123		"
3123	3161		"
3161	3205		"
3205	3238		"
3238	3274		"
3274	3313		"
3313	3346		"
3346	3387		"
3387	3448		"
3448	3479		"
3479	3518		"
3518	3554		"
3554	3582		"
3582	3593		"
3593	3622		"
3622	3648		Hard lime
3648	3656		" "
3656	3676		Lime
3676	3691		"
3691	3695		"
3695	3717		"
3717	3731		"
3731	3746		"
3746	3762		Broken Lime
3762	3786		Lime
3786	3802		"
3802	3840		Broken Lime