

OIL CONSERVATION DIVISION  
P. O. BOX 2038  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-73

|                        |  |
|------------------------|--|
| NO. OF COPIES RECEIVED |  |
| DISTRIBUTION           |  |
| SANTA FE               |  |
| FILE                   |  |
| U.S.G.S.               |  |
| LAND OFFICE            |  |
| OPERATOR               |  |

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEPLETION OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator  
Chevron U.S.A. Inc.

Address of Operator  
P.O. Box 670 Hobbs, NM 88240

Location of Well

UNIT LETTER U 660 FEET FROM THE South LINE AND 660 FEET FROM  
THE West LINE, SECTION 3 TOWNSHIP 21S RANGE 36E

7. Unit Agreement Name  
Eunice Monument South

8. Farm or Lease Name Unit

9. Well No.  
262

10. Field and Pool, or Widened  
Eunice Monument G/SA

15. Elevation (Show whether DF, RT, GR, etc.)

3572

12. County  
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

ORM REMEDIAL WORK ☐  
FORABLY ABANDON ☐  
OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

THAT sqz zones 1-4, recomp zone 1-3 ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

It is proposed to squeeze off the entire interval 3668-3814, TIH and drill out squeeze to  $\pm$  3778'. Perf 5 1/2" liner f/3767-3772, w/1 SPF, 180° phasing (5 holes). Acidize w/400 gallons 15% NEFE HCL, swab back and report results to office. Decision to keep zone 3 or squeeze off will be made at this time. Set CIBP at 3750, perf zones 1&2 w/4" guns at 3668-70, 3686-88, 3692-94, 3698-3723, 3731-41 (41 holes). Acidize w/ 2000 gallons 15% NEFE HCL. Swab back and report results, recover RBP and drill out CIBP, TIH w/ prod. equipment.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

M. E. Ahn

TITLE Staff Drilling Engineer

DATE March 16, 1988

COPIES BY DISPATCH  
SIGNATURES OF APPROVAL, IF ANY:

TITLE

DATE