MEXICO OIL CONSERVATION CO-MISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations

NOTICE OF INTENTED N TO TEST CA	SING SHUT-OFF	X NOTICE	OF INTENT	TON TO SHOO EAT WELL	OT OR
NOTICE OF INTENTION TO CHANGI	E PLANS	NOTICE	OF INTENT	ON TO PULL OF CASING	0B
NOTICE OF INTENTION TO BEPAIR	R WELL	·			
NOTICE OF INTENTION TO DEEPER	N WELL		OF INTENTI	ON TO PLUC V	VELL
-		Dallas, Tex	as.	Oet. 12	, 1956.
OIL CONSERVATION COMMISSION	N,	-			Date
anta Fe, New Mexico.					
entlemen:					
ollowing is a notice of intentiton to	to do certain work	as described below A. Akons	at the		
Company or Operator	Lease	A. ALUES	Well No		in SE/4
Sec. 5 , T. 21-8	_ 36-R	, N. M. P. M.	,1	funi ce	
Loa	County.	*			F
9-5/8" OD casi; using 400 sack;	ng set and S Of cement		damah .	4 0700 -	oot,
9-5/8" OD casi:	he set and	comented at	damah .	4 0700 -	oot,
9-5/8" OD casi:	ng set and S Of cement	cemented at	damah .	4 0700 -	••t,
9-5/8" OD casi; using 400 sacks	ng set and S Of cement	cemented at	damah .	4 0700 -	eet,
9-5/8" OD casi; using 400 sack:	ng set and S Of cement	cemented at	damah .	4 0700 -	eet,
9-5/8" OD casi; using 400 sack:	ng set and S Of cement	cemented at	damah .	4 0700 -	eet,
9-5/8" OD casi; using 400 sack;	ng set and S Of cement	cemented at	damah .	4 0700 -	eet,
9-5/8" OD casi; using 400 sack:	ng set and S Of cement	cemented at	damah .	4 0700 -	eet,
9-5/8" OD casi; using 400 sack:	ng set and S Of cement	cemented at	damah .	4 0700 -	eet,
9-5/8" OD casi; using 400 sack:	ng set and S Of cement	cemented at	damah .	4 0700 -	•et,
9-5/8" OD casi; using 400 sack;	ng set and S Of cement	cemented at	damah .	4 0700 -	•et,
9-5/8" OD casi; using 400 sack:	ng set and s of cement t. 16, 1936	cemented at	damah .	4 0700 -	•• t ,
9-5/8" OD casing using 400 sacks shut-off on Oct	ng set and s of cement t. 16, 1936	cemented at . Will be	depth of tested f	f 2595 f	eet,
9-5/8" OD casing using 400 sacks shut-off on Oct	ng set and s of cement i. 16, 1936	cemented at . Will be	depth of tested f	f 2595 f	eet,
9-5/8" OD casing using 400 sacks shut-off on Oct	ng set and s of cement i. 16, 1936	cemented at Will be	depth of tested f	CAPANY	eet,
9-5/8" OD casing using 400 sacks shut-off on Oct	ng set and s of cement i. 16, 1936	By	depth of tested f	T 2595 for water	eet,
9-5/8" OD casing 400 sacks shut-off on Oct	eg set and coments. 16, 1936	By	depth of tested f	T 2595 for water papary or opera parintend ations regardi	eet,

And the second of the second o

A COMPANIE OF THE STATE

and the second s

The second secon

A CAMPAGE AND A SECTION OF THE SECTI