

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions
reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.
LC 031740 (6)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☒ OIL WELL ☒ GAS WELL ☐ OTHER
2. NAME OF OPERATOR
CONTINENTAL OIL COMPANY
3. ADDRESS OF OPERATOR
Box 460, HOBBS, N.M. 88240
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1980' FSL & 1980' FEL OF SEC. 4

7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
MEYER B-4
9. WELL NO.
7
10. FIELD AND POOL, OR WILDCAT
EUNICE MONUMENT GAS
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 4, T-21S, R-36E
12. COUNTY OR PARISH
LEA
13. STATE
N.M.

14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3588' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other) **SET LINER & DEEPEN**

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Squeezed Eunice Gas Zone perfs 3336'-3510' w/150 sks. Class "C" cement. Did not hold press. Re-squeezed w/ 75 sks class "C" cement, drilled out cmt, press. to 1000#, held ok. Drilled new hole to 3946'. Ran 252' of 4 1/2" 10.23# Hx FS Liner. Stuck @ 3800', top of liner @ 3548'. Drilled out cmt 3792'-3940'. Perf open hole 3915', 20', 25', 30', 3935'. Treated w/ 500 gals 28% NE Acid. Ran plug, open ended, to 3935' & spotted 20 sks. Cl. "C". Drld. w/ 3 1/8" Bit 3714'-3890'. Perf. O-H @ 3845', 50', 55', 60', 65', 70', 75', 80', & 3885'. Set plv @ 3715' & treated w/ 2500 gals 28% NE Acid. Swabbed, install pumping equip. & returned to production. Work started 6-21-73, completed 7-11-73.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
OCT 1 1974
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

USGS-5, NMPL-4, File