	•.	بست حري بد حد حد المحمد	Form approved. Budget Bureau No	. 1004-0135
	UI ED STATES RTMEnt OF THE INTER			1, 1985
BU	REAU OF LAND MANAGEMEN	REASING	LC031740B	
	OTICES AND REPORTS (proposals to drill or to deepen or plug b PLICATION FOR PERMIT-" for such p)6. IF INDIAN, ALLOTTEE (DE TRIBE NAME
OIL CJ GAB	<u></u>	SEP 18 11 05 1	17. ORIT AGREEMENT NAM	
NAME OF OPERATOR		CARLELA	Eunice Monumen	<u>t South U</u> ni
hevron U.S.A. Inc.		AREA READOUAR	ERS 9. WBLL NO.	
.0. Box 670, Hobbs,	New Mexico 882/0			
LOCATION OF WELL (Report locat See also space 17 below.)	tion clearly and in accordance with any	State requirements.*	10. FIBLD AND POOL, OR	WILDCAT
At surface	and 1980 FWL		Eunice Monumen	
4620 S			11. SEC., T., R., M., OR BLI SURVEY OR AREA	
70000			Sec 4, T21S,R3	65 .
PERMIT NO.	15. ELEVATIONS (Show whether DF	, ET, GR, etc.)	12. COUNTY OF PARISH	
	3557'		Lea	NM
Check	Appropriate Box To Indicate N	lature of Notice, Report, or C	Other Data	
	INTENTION TO :		UBNT REPORT OF:	•
TEST WATER SHUT-OFF	PELL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WE	LL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CAS	INGE
SHOOT OR ACIDIZE	ABANDON®	SHOOTING OR ACIDIZING	ABANDONMENT	•
REPAIR WELL	CHANGE PLANS	(Other)	of multiple completion on	m Lan
(Other) run liner, pe	D OPERATIONS (Clearly state all parting	Completion or Recoupt	letion Report and Log form	<u>)</u>
proposed work. If well is di nent to this work.) *	rectionally drilled, give subsurface locat	tions and measured and true vertic	al depths for all markers a	and topics perti-
			1	
		· · · · · · · · · · · ·	រ១៩ សាក	<u> </u>
	ed to log and run a 4" rg water zones and perfo			
(The proposed	d procedure is as follow	vs: POOH w/productio	n tubing, TIH	
with 4 3/4" b	oit, drill out CIBP at 3	3730 [•] , push same to P	BTD at 3815.	
	B.6# CKF, POOH, Run CNL			
2 repeals tro	om TD - 3400'. Logs wil run 4" liner as follows:	I De evaluated for p	erts di inis t landing - 4	
				0
				Cra
collar, +- 35	50' liner, setting sleev r on bottom, circulate 1	/e w/ running tool on	2 7/ 8 NSER 5 7	RE RE
collar, +- 35 WS, Set liner Cement liner	50' liner, setting sleev r on bottom, circulate 1 w/ +- 50sx Class C w/ac	/e w/ running tool on L 1/2 times tubing an Iditives, Drop tubing	2 7/ 8 NSPE d liner capacity wiper plugand	+ m 0
collar, +- 35 WS, Set liner Cement liner displace w/ I	50' liner, setting sleev r on bottom, circulate 1 w/ +- 50sx Class C w/ac FW, engage liner and wip	ve w/ running tool on L 1/2 times tubing an dditives, Drop tubing ber plug and bump plu	2 7/ 8 NSPE d liner capacity wiper plugand gs in landing a	+ m 0
collar, +- 35 WS, Set liner Cement liner displace w/ F collar. Stir	50' liner, setting sleev r on bottom, circulate 1 w/ +- 50sx Class C w/ac FW, engage liner and wip ng out of setting sleeve	ve w/ running tool on L 1/2 times tubing an dditives, Drop tubing ber plug and bump plu e, POOH, WOC +-24-hou	2 7/ 8 NSPE d liner capacity wiper plugand gs in landing a	+ m 0
collar, +- 35 WS, Set liner Cement liner displace w/ H collar. Stir procedure to	50' liner, setting sleev r on bottom, circulate 1 w/ +- 50sx Class C w/ac FW, engage liner and wip ng out of setting sleeve follow based on log res	ve w/ running tool on L 1/2 times tubing an dditives, Drop tubing per plug and bump plu e, POOH, WOC +-24-hou sults.)	2 7/ 8 NSP d liner capacity wiper plug and gs in landing rs. Completion	ECE
collar, +- 35 WS, Set liner Cement liner displace w/ H collar. Stir procedure to Liner will be	50' liner, setting sleev r on bottom, circulate 1 w/ +- 50sx Class C w/ac FW, engage liner and wip ng out of setting sleeve follow based on log res set approx. from 3300'	ve w/ running tool on L 1/2 times tubing an dditives, Drop tubing per plug and bump plu e, POOH, WOC +-24-hou sults.) to 3815'. The perfo	2 7/ 8 NSP d liner capacity wiper plugand gs in landing rs. Completion ed interval	
collar, +- 35 WS, Set liner Cement liner displace w/ H collar. Stir procedure to Liner will be	50' liner, setting sleev r on bottom, circulate 1 w/ +- 50sx Class C w/ac FW, engage liner and wip ng out of setting sleeve follow based on log res	ve w/ running tool on L 1/2 times tubing an dditives, Drop tubing per plug and bump plu e, POOH, WOC +-24-hou sults.) to 3815'. The perfo	2 7/ 8 NSP d liner capacity wiper plug and gs in landing rs. Completion	
collar, +- 35 WS, Set liner Cement liner displace w/ H collar. Stir procedure to Liner will be	50' liner, setting sleev r on bottom, circulate 1 w/ +- 50sx Class C w/ac FW, engage liner and wip ng out of setting sleeve follow based on log res set approx. from 3300'	ve w/ running tool on L 1/2 times tubing an dditives, Drop tubing per plug and bump plu e, POOH, WOC +-24-hou sults.) to 3815'. The perfo	2 7/ 8 NSP d liner capacity wiper plugand gs in landing rs. Completion ed interval	
collar, +- 35 WS, Set liner Cement liner displace w/ H collar. Stir procedure to Liner will be will be from	50' liner, setting sleever on bottom, circulate 1 w/ +- 50sx Class C w/ac FW, engage liner and wip ng out of setting sleever follow based on log res e set approx. from 3300' approx. 3600' to 3800'.	ve w/ running tool on L 1/2 times tubing an dditives, Drop tubing per plug and bump plu e, POOH, WOC +-24-hou sults.) to 3815'. The perfo	2 7/ 8 NSP d liner capacity wiper plugand gs in landing rs. Completion ed interval	
collar, +- 35 WS, Set liner Cement liner displace w/ H collar. Stir procedure to Liner will be will be from	50' liner, setting sleever r on bottom, circulate 1 w/ +- 50sx Class C w/ac FW, engage liner and wip ng out of setting sleever follow based on log res e set approx. from 3300' approx. 3600' to 3800'.	ve w/ running tool on L 1/2 times tubing an dditives, Drop tubing per plug and bump plu e, POOH, WOC +-24-hou sults.) to 3815'. The perfo	2 7/ 8 NSP d liner capacity wiper plugand gs in landing rs. Completion ed interval	ECEIVED
<pre>collar, +- 35 WS, Set liner Cement liner displace w/ H collar. Stir procedure to Liner will be will be from </pre>	50' liner, setting sleever r on bottom, circulate 1 w/ +- 50sx Class C w/ac FW, engage liner and wip ng out of setting sleever follow based on log res e set approx. from 3300' approx. 3600' to 3800'.	ve w/ running tool on 1 1/2 times tubing an dditives, Drop tubing per plug and bump plu e, POOH, WOC +-24-hou sults.) to 3815'. The perfo	2 7/ 8 NSP d liner capaCity wiper plugtand gs in landing rs. Completion ed interval	ECEIVED
collar, +- 35 WS, Set liner Cement liner displace w/ H collar. Stir procedure to Liner will be will be from	50' liner, setting sleever r on bottom, circulate 1 w/ +- 50sx Class C w/ac FW, engage liner and wip ng out of setting sleever follow based on log res e set approx. from 3300' approx. 3600' to 3800'.	ve w/ running tool on 1 1/2 times tubing an dditives, Drop tubing per plug and bump plu e, POOH, WOC +-24-hou sults.) to 3815'. The perfo	2 7/ 8 NSP d liner capaCity wiper plugand gs in landing rs. Completion ed interval	ECEIVED
<pre>collar, +- 35 WS, Set liner Cement liner displace w/ H collar. Stir procedure to Liner will be will be from I bereby certify that the foregol SIGNED</pre>	50' liner, setting sleever r on bottom, circulate 1 w/ +- 50sx Class C w/ac FW, engage liner and wip ng out of setting sleever follow based on log res e set approx. from 3300' approx. 3600' to 3800'.	ve w/ running tool on 1 1/2 times tubing an dditives, Drop tubing per plug and bump plu e, POOH, WOC +-24-hou sults.) to 3815'. The perfo	2 7/ 8 NSP d liner capaCity wiper plugtand gs in landing rs. Completion ed interval	ECEIVED

.

.....

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

