

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well <input checked="" type="checkbox"/> gas well <input type="checkbox"/> other <input type="checkbox"/>	5. LEASE LC-031740 6
2. NAME OF OPERATOR Conoco Inc.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P.O. Box 460, Hobbs, N.M. 88240	7. UNIT AGREEMENT NAME NMF-4
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 4620' FSL & 1980' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	8. FARM OR LEASE NAME Meyer B-4
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	9. WELL NO. 13
	10. FIELD OR WILDCAT NAME Eunice Monument (B-5A)
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 4, T-21S, R-36E
	12. COUNTY OR PARISH Lea
	13. STATE N.M.
	14. API NO.
	15. ELEVATIONS (SHOW DF, KDB, AND WD)

## REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
 FRACTURE TREAT ☐  
 SHOOT OR ACIDIZE ☐  
 REPAIR WELL ☐  
 PULL OR ALTER CASING ☐  
 MULTIPLE COMPLETE ☐  
 CHANGE ZONES ☐  
 ABANDON\* ☐  
 (other) ☐

## SUBSEQUENT REPORT OF:

☐  
☐  
☒  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED  
 FEB 11 1980  
 U. S. GEOLOGICAL SURVEY  
 HOBBS, NEW MEXICO

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MIRU 1-30-80. Tagged fill @ 3857'. Logged well from 3000'-3864'. Perf. 3730'-40', 3760'-80', 3805'-15', 3825'-35' w/ 1 JSPP (50 holes). Acidize w/ 118 bbls. 15% HCl-NE. Treated well w/ 34 bbls. scale inhibitor. With w/ slotted MA, SN, & 130 jts. 2 7/8" Ybg. set @ 3801'. SN @ 3770'

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Dutton TITLE Admin. Supervisor DATE 2/8/80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

U. S. GEOLOGICAL SURVEY  
 HOBBS, NEW MEXICO

\*See Instructions on Reverse Side

100-100000-100000

100

100-100000-100000

OIL CONSERVATION DIV.

FEB 19 '80

RECEIVED