

UNITED STATES NEW MEXICO 88240

DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
- 
2. NAME OF OPERATOR  
CONOCO INC.
- 
3. ADDRESS OF OPERATOR  
P. O. Box 460, Hobbs, N.M. 88240
- 
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 3300' FSL & 1980' FEL  
AT TOP PROD. INTERVAL: ✓  
AT TOTAL DEPTH: ✓
- 
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE  
LC-031740(b)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
NMFU
8. FARM OR LEASE NAME  
Meyer B-4
9. WELL NO.  
8
10. FIELD OR WILDCAT NAME  
Eunice Monument G-SA
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 4, T-21S, R-36E
12. COUNTY OR PARISH  
Lea
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input checked="" type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>

(other) Clean out & Inhibit

SUBSEQUENT REPORT OF:

□ □ □ □ □ □ □

MAR 16 1983

**OIL & GAS  
MINERALS MGMT. SERVICE  
ROSWELL, NEW MEXICO**

3 (NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*
- C.O. OH to 3852'. String shoot OH from 3852' to 3762'. CO  
OH to 3852'. Spot 2 Bbl. 15% HCL-NE-FE from 3852' to 3775'.  
Set pkr. @ 3700'. Pump 50 Bbl. 15% HCL-NE-FE. Pump 200 lbs  
graded rock salt mixed in 3 Bbl. 10 PPG brine water w/10 lbs  
guar gum. Pump 50 Bbls. 15% HCL-NE-FE. Flush w/35 Bbl. 2% KCL  
TFW. Swab. Chemically inhibit 3852'-3743'. Mix 1 drum chemical w/220  
Bbl. 2% KCL TFW. Pump 200 lbs. graded rock salt in 3 Bbl. 10 PPG brine  
water w/10 lbs. guar gum. Rel. pkr. @ 3700'. Run production Equipment.  
Test.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. H. G. Butterfield TITLE Administrative Supervisor DATE 3/15/83

APPROVED (This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

PROVAL, IF ANY.  
MAR 18 1963  
FOR  
JAMES A. GILLHAM  
DISTRICT SUPERVISOR

**\*See instructions on Reverse Side**

RECEIVED  
MAR 21 1983  
O.C.D.  
HOBBS OFFICE