Form	9-881 a
(Feb	. 1951)

1 1			
1			
1	X		;
			,
1	i	!	į.

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Form App	roved.	
Land Office	Las	Cruces
Lease No	031,	740 (b)
Unit	K	

Budget Bureau No. 42-R358.4.

AND DEDODTS ON WELLS

NAMES OF INTENTION TO DOUG	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO DRILL	A CONTRACTOR OF ACCUSANCE
NOTICE OF INTENTION TO CHARGE TESTION	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	The second secon
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	
NOTICE OF INTENTION TO PULL OR ALTER CASING	
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CH	IECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	September , 196
Vell No. 22 is located 3450 CT K Sec. 4 (1/8 Sec. and Sec. No.) (Twp.)	ft. from N line and 1980 ft. from W line of sec.
**	New Maxice
(Field)	(County or Subdivision) (State or Territory)
	, , ,
he elevation of the derrick floor above	DETAILS OF WORK
tate names of and expected depths to objective sand ing point	DETAILS OF WORK
tate names of and expected depths to objective sand ing point	DETAILS OF WORK Is; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, ceme ts, and all other important proposed work)
tate names of and expected depths to objective sand ing point of the second of the sec	DETAILS OF WORK des; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemests, and all other important proposed work) 130 Feb. 9-9-62. Drilled to 1260 and ran 1257
Spudded sever 8-4 80. 22 at 2 of 8 5/8" (D 24/ J-55 casing.	DETAILS OF WORK ls; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, ceme ts, and all other important proposed work) 130 F.M. 9-9-62. Drilled to 1260' and ran 1257 Caning set at 1260' and committed with 600 sac
tate names of and expected depths to objective sand ing point Spudded Sever Red Ro. 22 at 2 28 5/8* (D 24* J=55 casing.	DETAILS OF WORK Is; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemes, and all other important proposed work) 130 F.M. 9-9-62. Drilled to 1260' and ran 1257 Caming set at 1260' and camented with 600 sec. Plug down at 9:00 F.M. 9-10-62. 8.0.0. 24 hre.
tate names of and expected depths to objective sand ing point opposed depths opposed	DETAILS OF WORK Is; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemes, and all other important proposed work) 130 F.M. 9-9-62. Drilled to 1260' and ran 1257 Caming set at 1260' and camented with 600 sec. Plug down at 9:00 F.M. 9-10-62. 8.0.0. 24 hre.
tate names of and expected depths to objective sand ing point opposed depths opposed	DETAILS OF WORK Is; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemes, and all other important proposed work) 130 F.M. 9-9-62. Drilled to 1260' and ran 1257 Caming set at 1260' and camented with 600 sec. Plug down at 9:00 F.M. 9-10-62. 8.0.0. 24 hre.
tate names of and expected depths to objective sand ing point opened depths to objective sand ing point opened depths to objective sand ing point of the sand depths to objective sand ing point of the sand depths to objective sand ing point of the sand depths to objective sand ing point of the sand depths to objective sand ing point of the sand depths to objective sand ing point of the sand depths to objective sand ing point of the sand depths to objective sand ing point of the sand depths to objective sand ing point of the sand depths to objective sand ing point of the sand depths to objective sand ing point of the sand depths to objective sand depths	DETAILS OF WORK Is; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemes, and all other important proposed work) 130 F.M. 9-9-62. Drilled to 1260' and ran 1257 Caming set at 1260' and camented with 600 sec. Plug down at 9:00 F.M. 9-10-62. 8.0.0. 24 hre.
tate names of and expected depths to objective sand ing point opposited sever Fal. Ho. 22 at 2 of 8 5/6" (D 24 Ja55 casing. Demont circulated. Tested casing with 1000 PSI for the case of the casing with 1000 PSI for the case of the cas	DETAILS OF WORK Is; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemerate, and all other important proposed work) 130 F.M. 9-9-62. Drilled to 1260' and ran 1257 Caming set at 1260' and commuted with 600 saccompliance at 9:00 F.M. 9-10-62. W.C.C. 24 hreader 30 minutes before and after drilling plug.
ing point in purchased of the point ing point	DETAILS OF WORK Is; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemerate, and all other important proposed work) 130 F.H. 9-9-62. Drilled to 1260' and ran 1257 Caming set at 1260' and camented with 600 succepting down at 9:00 F.M. 9-10-62. W.C.C. 24 hreador 30 minutes before and after drilling plug. approval in writing by the Geological Survey before operations may be commenced.
tate names of and expected depths to objective sand ing point opened agree Fal. Ho. 22 at 2 of 8 5/6" (D 24 J-55 casing. Depend oneing with 1000 PSI for the standard of the	DETAILS OF WORK Is; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemerate, and all other important proposed work) 130 F.M. 9-9-62. Drilled to 1260' and ran 1257 Caming set at 1260' and camented with 600 saccoming down at 9:00 F.M. 9-10-62. W.C.C. 24 hreader 30 minutes before and after drilling plug. approval in writing by the Geological Survey before operations may be commenced.