

30 GAS - 07474
OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Federal ☒ Fee ☐
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☐ OTHER- Salt Water Disposal

Name of Operator
Chevron U.S.A. Inc.

Address of Operator
P.O. Box 670 Hobbs, NM 88240

Location of Well

UNIT LETTER W 660 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE. SECTION 4 TOWNSHIP 21S RANGE 36E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
3584

7. Unit Agreement Name
Eunice Monument South

8. Farm or Lease Name Unit SWD

9. Well No.
1

10. Field and Pool, or WHdcat
Eunice Monument (San And)

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

FORM REMEDIAL WORK ☐
PERMANENTLY ABANDON ☐
OR ALTER CASING ☐
THAT ☐
PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER Convert to Salt Water Disposal ☒
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Work performed 3-18-87 thru 3-24-87

POOH w/production equipment. Set CIBP at 5315', dump 35' cmt on CIBP. Run GR,CCL,CBL f/4800' to surf. Run CBL f/4800' to 3000', Test csg to 1000psi, ok. Perf w/4" guns, 4JHPF, 216 holes total in 5 zones at 4414-24, 4427-37,4448-58, 4464-78, 4480-90. Acidize w/8000 gallons 15% NEFE HCL. Perf w/ 3 3/8" guns 120° phased, 280 holes in 7 zones at 4526-40', 4546-56, 4558-72, 4582-90, 4594-4602, 4612-16, 4622-34. Acdz perfs f/4526- 4634 w/ 8500 gallons 15% NEFE HCL. Perf w/ 3 3/8" guns, 120° phased, 4 JHPF, 208 holes total in 5 zones at 4680-90, 4696-4706,4710-18, 4746-60, 4766-76, Acidize f/4680-4776 w/8000 gallons 15% HCL, swab. TIH w/ 2 7/8" IPC J-55, 6.5#, EUE 8rd tbg to 4369'. Pump 70bbbls pkr fluid, ND BOP, set pkr at 369' w/6000 comp, NU WH, load csg w/ pkr fluid, work air out, test 600psi f/30min, ok. RDMOPU. Left SI pending injection line hookup.

by M. E. Abin TITLE: Staff Drilling Engineer DATE: Sept. 6, 1988
by Jerry L. L... DISTRICT 1 SUPERVISOR
SIGNATURES OF APPROVAL, IF ANY: DATE: SLP 7/1