

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

| | |
|--------------------------------------|--|
| WELL API NO. | 30-025-04493 |
| 5. Indicate Type of Lease | STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No. | E-230 |
| 7. Lease Name or Unit Agreement Name | |
| EUNICE MONUMENT SOUTH UNIT | |
| 8. Well No. | 183 |
| 9. Pool name or Wildcat | EUNICE MONUMENT; GRAYBURG-SAN ANDRES |

| | |
|--|--|
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) | |
| 1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER INJECTOR | |
| 2. Name of Operator Chevron U.S.A. Inc. | |
| 3. Address of Operator P.O. Box 1150, Midland, TX 79702 | |
| 4. Well Location Unit Letter D : 660 Feet From The NORTH Line and 660 Feet From The WEST Line Section 4 Township 21S Range 36E NMPM LEA County | |
| 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3547' | |

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ADDED PERFS, ACZD, SQZD ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

POH W/TBG & INJ EQPT. PERFD 3700'-3708' W/3 JHPF. PICKLED TBG @ 3534' W/500 GALS 15%; ACZD PERFS & OH W/2000 GALS 15%. SPOTTED SD TO 3693'. SET CIBP @ 3692'. SET CIRC @ 3558'; PPD 150 SX CL "C", SQZD 133 SX IN FORM. DRILLED CIRC & CMT TO 3690'; TSTD SQZ 450#. DRILLED OUT CIBP & WASHED SD TO 3803'. CIRC CLEAN. RIH W/INJ TBG & PKR @ 3563'. RAN MIT. 350# - 15 MIN; PRESS TO 380#-OK. RETURNED WELL TO INJECTION.

WORK PERFORMED 10/29/97 - 11/10/97

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE J. K. Ripley TITLE TECHNICAL ASSISTANT DATE 1/19/98
TYPE OR PRINT NAME J. K. RIPLEY TELEPHONE NO. (915)687-7148

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: