

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-39

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-04493

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☐

OTHER ☒ Injection

2. Name of Operator

Chevron U.S.A. Inc.

3. Address of Operator

P. O. Box 670, Hobbs, NM 88240

4. Well Location

Unit Letter D : 660 Feet From The North Line and 660 Feet From The West Line

Section 4

Township 21S

Range 36E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3547

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Plugged back, added perfs, and acdz ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

09/27/89 - Rih w/bailer set 1.5sx sd (3837'-3829'), Rih w/bailer set 2lg hydromite cmt plug @ 3829', wait 1 hour, tag toc @ 3813', perf Zone 5-OH, 3790'-3800' & 3776'-80' (28 shots-2JPF-4"prem-180deg), 3668'-86' (36H-2JPF-4"prem-180deg)

09/28/89 - Perf Zone 4, 3732'-36', Zone 2, 3648'-54', 3610'-20', (40 holes-2JPF-4"prem-180deg), set 2lg hydromite plug (3827'-3791'), tag @ 3794', push to 3801'.

10/01/89 - Set & tst'd rbp @ 3704', spot 100g-15%nefe hcl (3692-3590'), set pkr @ 3566' acid 1 & 2 (3610'/3686') w/2450 gelled 16/7%(titr)nefe hcl. Turn well over to production

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE M. E. Akins

TITLE Staff Drilling Engineer

DATE 10/04/89

TYPE OR PRINT NAME M. E. Akins

TELEPHONE NO. 393-4121

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON,
DISTRICT I SUPERVISOR

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

OCT 6 1989