


SANTA FE, NEW MEXICO

AREA 640 ACRES
LOCATE WELL CORRECTLY

DEPARTMENT OF THE STATE GEOLOGIST

WELL RECORD

Mail to State Geologist, Santa Fe, New Mexico, not more than ten days

after completion of well. Indicate questionable data by fol-

lowing it with (?). Submit in duplicate.

Company **Atlantic Oil Producing Company** Address **Box 2819, Dallas, Tex. s.**
Send correspondence to **Above** Address **Above**
State "C" Well No. **C-2** in **SE/4 SE/4** of Sec. **5**, T. **21 South**
R. **36 East**, N. M. P. M. **Runico** Oil Field **Lea** County.
If State land the oil and gas lease is No. **B-1673** Assignment No. **-**
If patented land the owner is **-** Address **-**
The lessee is **State of New Mexico** Address **Santa Fe, New Mexico**
If not state or patented land, give status **-**
Drilling commenced **July 2nd,** 19 **35** Drilling was completed **August 5th,** 19 **35**
No 1 Comp. August 3, 1935
Name of drilling contractor **Bert Fields** Address **Dallas**
Elevation above sea level at top of casing **3585** feet.
The information given is to be kept confidential until **-** 19 **-**

OIL SANDS OR ZONES

No. 1, from **See log** to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

No. 1, from **See log** to No. 3, from to
No. 2, from to No. 4, from to

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATED		PURPOSE
							FROM	TO	
12-1/2"	50#	8thd	Lapweld	80'	Common	None	-	-	wtr. string
9-5/8"	56#	8thd	"	1584'	"	"	-	-	intern. "
7"	24#	8thd	S. S.	5775'	Halliburton	"	-	-	oil "

MUDDING AND CEMENTING RECORD

SIZE	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
12-1/2"	80'	150	Halliburton	?	?
9-5/8"	1584'	500	"	?	?
7"	5775'	800	"	?	?

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

SHOOTING RECORD

SIZE	SHELL USED	EXPLOSIVE USED	QUANTITY	DATE	DEPTH SHOT	DEPTH CLEANED OUT
------	------------	----------------	----------	------	------------	-------------------

NOT SHOT OR ACIDIZED

TOOLS USED

Rotary tools were used from **0** feet to **3585** feet, and from **-** feet to **-** feet
Cable tools were used from **-** feet to **-** feet, and from **-** feet to **-** feet

PRODUCTION

Put to producing **August 8th,** 19 **35**
I. P. test 35 bbls. per hour natural
The production of the first 24 hours was **100** barrels of fluid of which **-**% was oil: **-**%
emulsion: **-**% water; and **-**% sediment. Gravity. Be. **-**
If gas well, cu. ft. per 24 hours **-** Gallons gasoline per 1,000 cu. ft. of gas **-**
Rock pressure, lbs. per sq. in. **-**

EMPLOYES

T. O. Hoffman - P. G. Powell, Driller **C. M. Mills - A. C. Bradford**, Driller
M. R. Hastings, Driller **Carl Robinette**, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and
all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this **20th** day of **September**, 19 **35**
Name **J. B. Beech**
Position **Drilling & Production Department**
Representing **Atlantic Oil Producing Company**
Company or Operator
My commission expires **June 1, 1937** Notary Public

FORMATION RECORD

From	to	Thickness in Feet	Formation
0		80	Surface soil
80		96	White surface rock
96		164	Sand
164		186	Sand
186		366	Red bed & shells
366		730	Sand and red bed
730		882	Red bed and shells
882		1150	Red rock
1150		1238	Red rock & red bed
1238		1330	Anhydrite
1330		1385	Anhydrite & salt
1385		1406	Salt
1406		1585	Salt & anhydrite shells
1585		1902	Salt & potash
1902		2283	Salt, potash & anhydrite
2283		2465	Salt & anhydrite
2465		2559	Salt & anhydrite shells
2559		2799	Anhydrite
2799		2845	Anhydrite & streak of sand
2845		2850	Anhydrite & lime, showing gas
2850		2893	Anhydrite & streaks lime
2893		2990	Anhydrite & brown lime
2990		3090	Anhydrite & lime
3090		3123	Brown lime
3123		3201	Anhydrite & lime
3201		3393	Brown lime
3393		3422	Sand & sandy lime
3422		3810	Gray lime
3810		3885	Gray lime