

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

	State "H"

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Atlantic Oil Producing Company

Box 2819, Dallas, Texas.

Company or Operator

Address

State "H"

Well No. 5

NW/4 of NE/4 Sec. 5

T. 21 S

Lease

R. 36 E

Eunice

Field,

Lea

County.

Well is 660

feet south of the North line and 1980

feet west of the East line of Sec. 5-21S-36E

If State land the oil and gas lease is No. B-2159

Assignment No. -

If patented land the owner is -

Address

If Government land the permittee is -

Address

The Lessee is -

Address

Drilling commenced Dec. 21

19 35

Drilling was completed

January 18th

19 36

Name of drilling contractor Bert Fields

Address

Dallas, Texas

Elevation above sea level at top of casing 3584 feet.

The information given is to be kept confidential until

19

## OIL SANDS OR ZONES

No. 1, from see log

to

No. 4, from

to

No. 2, from

to

No. 5, from

to

No. 3, from

to

No. 6, from

to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from see log

to

feet.

No. 2, from

to

feet.

No. 3, from

to

feet.

No. 4, from

to

feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
12 1/2"	50 1/2	8	Lapweld	252'	common	none	none	-	Wtr. strg.
8-5/8"	50 1/2	10	"	1365'	"	"	"	-	Intern.
5-1/2"	37 1/2	10	SS	3792'	Halliburton	"	"	-	Oil
2-1/2"	Tubing		SS	3878'					

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	12 1/2"	252'	150	Halliburton		
	8-5/8"	1365	800	"		
	5 1/2"	3792	800	"		

## PLUGS AND ADAPTERS

Heaving plug—Material

Length

Depth Set

Adapters—Material

Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from - feet to 3894 feet, and from - feet to - feet

Cable tools were used from - feet to - feet, and from - feet to - feet

## PRODUCTION

Put to producing January 18th, 1936

The production of the first 24 hours was 296 barrels of fluid of which 100 % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

## EMPLOYEES

R. C. Watson, Driller C. B. C. sby, Driller

, Driller J. S. Galbraith, Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 25

Dallas, Texas

February 1936

day of February, 1936

Name J. A. Seale

Position Operating Department

Representing Atlantic Oil Producing Company

Company or Operator

My Commission expires June 1, 1937

Address Box 2819, Dallas, Texas.

In and for Dallas County, Texas.

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	20		Surface
20	230		Sand , shale and red beds
230	282		Shale and shells
282	502		Red Beds, shale and shells
502	770		Red beds and sand
770	962		Red beds and red rock
962	1062		Red bed, red rock and shells
1062	1150		Red Beds and red rock
1150	1207		Anhydrite and lime
1207	1365		Red rock, lime and anhydrite
1365	1594		Salt and Anhydrite
1594	1815		Salt and Anhydrite
1815	2100		Anhydrite and salt
2100	2273		Salt, anhydrite and shells
2273	2297		Salt and anhydrite
2297	2311		Salt
2311	2344		Salt and anhydrite
2344	2480		Salt and anhydrite
2480	2550		Salt
2550	2545		Anhydrite
2545	2622		Gyp and Anhydrite
2622	2652		Anhydrite and potash
2652	2724		Gyp and anhydrite
2724	2768		Anhydrite and lime
2768	2803		Gyp, anhydrite and lime
2803	2957		Lime and anhydrite
2957	3025		Gray lime
3025	3071		Lime
3071	3100		Gray lime
3100	3133		Gray and brown lime
3133	3205		Lime
3205	3235		Gray and brown lime
3235	3273		Lime
3273	3345		Brown lime
3345	3375		Lime
3375	3403		Brown lime
3403	3443		Gray and brown lime
3443	3471		Lime
3471	3504		Brown lime and potash
3504	3579		Brown lime
3579	3604		Gray and brown lime
3604	3726		Brown lime
3726	3750		Gray lime
3750	3800		Gray and brown lime
3800	3894		Lime
	3894		TOTAL DEPTH