Form C-102

NEW TXICO OIL CONSERVATION COMPTSSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature				
OTICE OF INTENTION TO TEST CASING SHUT-OFF	X NOT	ICE OF INTENTION CHEMICALLY TREAT	TO SHOOT OR WELL	
TICE OF INTENTION TO CHANGE PLANS	гол	TICE OF INTENTION OTHERWISE ALTER	TO PULL OR CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL		
OTICE OF INTENTION TO DEEPEN WELL				
Mid la	nd, Texas	Feb.	ruary 22, 19	936
IL CONSERVATION COMMISSION,				
entlemen: ollowing is a notice of intentiton to do certain wo Devonian Oil Company Heas			Z C T	
Companyor Operator on a				Lot #1
Sec, T, R	, N. M.	P. M.,	Eunice	Field,
LeaCounty.				
We expect to test surface ruary 24th, 1936. Total dept feet and its size will be 17 fifty pound second hand pipe 200 sacks of cement. We plan and this will be set at approximately approximately second seco	th of the inch. The and will to run a	hole will be nis surface of be comented to our oxima tely	approximate casing will to the surfa 250 feet of	ely 300 be 12½ ce with pipe
ruary 24th, 1936. Total dept feet and its size will be 17, fifty pound second hand pipe 200 sacks of cement. We plan	inch. The and will a to run apprimately and plug mand pl	hole will be ais surface of the cemented to proximately 270 feet. Coethod. This before pluggers	a proximate casing will to the surfa 250 feet of ementing will string of p s are drille	be 12½ to the pripe of and w
ruary 24th, 1936. Total dept feet and its size will be 172 fifty pound second hand pipe 200 sacks of cement. We plan and this will be set at approduce by Haliburton, by pump a shall stand cemented at least then be tested for water shut to stand for one hour.	th of the inch. The inch. The inch. The inch. The inch. The inch is and will in to run appearance of the inch inch inch inch inch inch inch inch	hole will be his surface to comented to proximately 270 feet. Coethod. This before pluggemptying the	a proximate casing will to the surfa 250 feet of ementing will string of p s are drille	ely 300 be 12½ ce with pipe l be oipe d and w lowing
ruary 24th, 1936. Total dept feet and its size will be 172 fifty pound second hand pipe 200 sacks of cement. We plan and this will be set at approdone by Haliburton, by pump a shall stand cemented at least then be tested for water shut to stand for one hour. Approved—except as follows:	th of the inch. The inch. The inch. The inch. The inch. The inch is and will in to run appearance of the inch inch inch inch inch inch inch inch	be cemented to proximately 270 feet. Coethod. This before pluggemptying the	approximate casing will to the surface 250 feet of ementing will string of pare drille hole and al	ely 300 be 12½ ce with pipe l be oipe d and i
ruary 24th, 1936. Total dept feet and its size will be 172 fifty pound second hand pipe 200 sacks of cement. We plan and this will be set at approduce by Haliburton, by pump a shall stand cemented at least then be tested for water shut to stand for one hour.	sh of the inch. The inch. The inch. The inch. The inch. The inch is and will in to run approximately and plug mand p	be cemented to proximately 270 feet. Coethod. This before pluggemptying the DEVONIAN DEVONIAN Send communication Send communication Send communication	approximate casing will to the surface 250 feet of ementing will string of pare drille hole and al	ely 300 be 12½ ce with pipe l be oipe d and w lowing
ruary 24th, 1936. Total dept feet and its size will be 172 fifty pound second hand pipe 200 sacks of cement. We plan and this will be set at approdone by Haliburton, by pump a shall stand cemented at least then be tested for water shut to stand for one hour. Approved—except as follows:	sh of the inch. The inch. The inch. The inch. The inch. The inch is and will in to run approximately and plug mand p	be cemented to proximately 270 feet. Coethod. This before pluggemptying the	approximate casing will to the surface 250 feet of ementing will string of pare drille hole and all on the case of	ely 300 be 12½' ce with pipe l be oipe d and v lowing

DOBATTERS WELLTYCK CONTROL OF A STANDARD មនេះស្រីស្រែក ខ្លាំនៃ សម្បើប

230 FOR LOW OF THOMPS

inder to the end of the control of the end o

18 特别 \$4 (4) \$1 (1) (1) (1) (1) (1) (1) (1)

· · · · · · · · · · · · · · · · · · ·	11 15.	And the second s
		erinari erin erinari erin erin erin erin erin erin erin er
COMPANIES OF SECURITY SECTIONS		
and the same of th		And the state of t

A Mark A Color of the Color of

The second of th

PROMES DUSCOSSIONS TO SERVICE SERVICE

A SASTED BOOKS AND COMES OF SMITH CONTROL OF THE CONTROL OF SMITH CONTROL OF S

 $\left(\frac{1}{2} + \cdots + \frac{1}{2} + \cdots + \frac{1}{2}\right) = 0$

ne de la la companya de la companya The continuous state successor, yet and

> ورباء وأواك والسار الماك والمحطوفين CATHORITON AND THE COLOR The second The second secon