

Submit 3 Copies To Appropriate District

Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

811 South First, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-025-04522

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Eunice Monument
South Unit

8. Well No. 192

9. Pool name or Wildcat Eunice
Monument, Grayburg SA

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Chevron USA, Inc.

3. Address of Operator

15 Smith Rd., Midland, Texas 79705

4. Well Location

Unit Letter E : 1980 feet from the North line and 660 feet from the West line

Section 6

Township 21S Range 36E

NMPM Lea County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Notify OCD 24 hrs prior to MI & RU.
2. Set 5 1/2" CIBP @ 3700' (Grayburg-San Andres) Spot 30 Sx plug 3700'-3400' (Queen) WOC Tag.
3. Displace hole w/MLF, 9.5# Brine w/25# Gel P/BBL.
4. Spot 25 Sx plug 2600'-2400' (B-Salt) WOC Tag.
5. Spot 30 Sx plug 1325'-1100' (8 5/8" Shoe, T-Salt) WOC Tag.
6. Spot 35 Sx plug 350'-Surf (12 1/2" Shoe, Surface) WOC.
7. Install dry hole marker.

THE COMPLETION MUST BE NOTIFIED 24
HOURS PRIOR TO THE BEGINNING OF
PLUGGING OPERATIONS FOR THE C-103
TO BE APPROVED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE A.R. Bledsoe

TITLE HES Specialist

DATE 5/31/2002

Type or print name G.R. Bledsoe

Telephone No. 915.682.7153


(This space for State use) SIGNED BY

GARY W. WINK

APPROVED BY OC FIELD REPRESENTATIVE II/STAFF MANAGER

Conditions of approval, if any:

DATE JUN 04 2002



LOGGING & ABANDONMENT WORKSHEET

OPERATOR CHEVON USA INC.
 LEASE NAME EMWEE MONUMENT SOUTH UNIT
 WELL # 192

SECT 6 TWN 21-S RNG 36-E
 FROM 1980 N/S L 660 E/W L
 TD 3967 FORMATION @ TD SAN ANDRES
 PBTD FORMATION @ PBTD Grayburg

	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	12 1/2	277'	SURF	Ciec
INTMED 1	8 5/8	1251	SURF	Ciec
INTMED 2				
PROD	5 1/2	3754	SURF	Ciec.

	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1					
LINER 2					

	CUT & PULL	TOP - BOTTOM
INTMED 1	PERFS	
INTMED 2		
PROD	OPENHOLE	3754 - 3967

*REQUIRED PLUGS DISTRICT

	PLUG	TYPE PLUG	SACKS CEMENT	DEPTH
RUSTLER (ANHYD)	1	CIBP		3700
YATES	2	QUEEN	30	3700
QUEEN	3	B-SALT	25	2600
GRAYBURG	4	8 5/8 SHOE	30	1325
SAN ANDRES	5	12 1/2 SHOE	25	350
CAPITAN REEF				
DELAWARE				
BELL CANYON				
CHERRY CANYON				
BRUSHY CANYON				
BONE SPRING				
GLORIETA				
BLINBRY				
TUBB				
DRINKARD				
ABO				
WC				
PENN				
STRAWN				
ATOKA				
MORROW				
MISS				
DEVONIAN				

12 1/2
 @ 277
 TOC SURF

8 5/8
 @ 1251
 TOC SURF

5 1/2
 @ 3754
 TOC SURF

TD 3967

