

NEW MEXICO OIL CONSERVATION COMMISSION									
SANTA FE, NEW MEXICO									
<p>AREA 640 ACRES LOCATE WELL CORRECTLY</p>		WELL RECORD				<p>DUPLICATE</p>			
<p>Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following instructions SUBMIT IN TRIPLICATE.</p>									
Gulf Oil Corporation		Company or Operator		Well No. 560		Sec. 6		T. 21N	
R. R. Bell		Lease		B-250		County. NM SE			
Well is 560 feet south of the North line and 560 feet west of the East line of									
If State land the oil and gas lease is No. B-250 Assignment No. _____									
If patented land the owner is _____ Address _____									
If Government land the permittee is _____ Address _____									
The Lessee is Gulf Oil Corporation Address Tulsa, Oklahoma.									
Drilling commenced Sept. 27, 19 36 Drilling was completed Nov. 2nd, 19 36									
Name of drilling contractor Lee Drig. Co. Address Tulsa, Oklahoma.									
Elevation above sea level at top of casing 5577' feet.									
The information given is to be kept confidential until _____ 19 ____									
OIL SANDS OR ZONES									
No. 1, from 5775 to 5880 No. 4, from _____ to _____									
No. 2, from Pay 5780' to _____ No. 5, from _____ to _____									
No. 3, from _____ to _____ No. 6, from _____ to _____									
IMPORTANT WATER SANDS									
Include data on rate of water inflow and elevation to which water rose in hole.									
No. 1, from Rotary hole to _____ feet.									
No. 2, from _____ to _____ feet.									
No. 3, from _____ to _____ feet.									
No. 4, from _____ to _____ feet.									
CASING RECORD									
SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED TO	PURPOSE	
10-3/4	52	8	Lagw.	256					
7-5/8	22	8	Lagw.	1504					
5-1/2	17	10	Lagw.	5775					
MUDDING AND CEMENTING RECORD									
SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED			
10-3/4	10-3/4	256	250	Halliburton					
7-5/8	7-5/8	1504	206	"					
5-1/2	5-1/2	5775	230	"					
PLUGS AND ADAPTERS									
Heaving plug—Material _____ Length _____ Depth Set _____									
Adapters—Material _____ Size _____									
RECORD OF SHOOTING OR CHEMICAL TREATMENT									
SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT			
Results of shooting or chemical treatment _____									
RECORD OF DRILL-STEM AND SPECIAL TESTS									
If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.									
TOOLS USED									
Rotary tools were used from 0 feet to 5880 feet, and from _____ feet to _____ feet									
Cable toops were used from _____ feet to _____ feet, and from _____ feet to _____ feet									
PRODUCTION									
Put to producing Nov. 16th, 19 36									
The production of the first 24 hours was 522 barrels of fluid of which _____ % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be _____									
If gas well, cu. ft. per 24 hours 735,000 Gallons gasoline per 1,000 cu. ft. of gas _____									
Rock pressure, lbs. per sq. in. _____									
EMPLOYEES									
_____, Driller _____, Driller									
_____, Driller _____, Driller									
FORMATION RECORD ON OTHER SIDE									
I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.									
Subscribed and sworn to before me this 18th,				Place Tulsa, Oklahoma Date Dec. 18th, 1936					
day of December , 19 36				Name D. R. Darden					
J. W. Evans				Position General Superintendent					
Notary Public				Representing Gulf Oil Corporation					
My Commission expires March 16, 1940				Company or Operator _____					
				Address Tulsa, Oklahoma.					

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	185		Caliche and sand
	260		red rock
	525		red rock and shells
	750		red rock
	1250		red rock and shells
	1570		anhydrite
	1590		salt
	2500		salt and shells
	2740		anhydrite and gyp
	2845		anhydrite and gyp
	2995		brown line
	3025		line, gray and sandy
	3450		line, gray
	3476		sandy line
	3580		gray line