

N.

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

Center of Lot 8	

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Gulf Oil Corporation

Orcutt C

Company or Operator

Lease

Well No. 1 in Lot 8 of Sec. 6, T. 21S

R. 36E, N. M. P. M., Eunice Field, Lea County.

Well is feet south of the North line and feet west of the East line of Center of Lot No. 8

If State land the oil and gas lease is No. B-244 Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Gulf Oil Corporation Address Tulsa, Oklahoma.

Drilling commenced Aug. 14th, 1936 Drilling was completed Oct. 4th, 1936

Name of drilling contractor Sparkman and Hensch Address Tulsa, Oklahoma.

Elevation above sea level at top of casing 3588 feet.

The information given is to be kept confidential until 19

## OIL SANDS OR ZONES

No. 1, from 3735 to 3870 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from Rotary hole to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED TO	PURPOSE
13-3/8	50	8	Lapweld	39'	?			
7-5/8	22	8	"	1182'				
5-1/2	17	10	"	3753'				

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
?	13-3/8	39'	60	Dump bailer		
9-7/8	7-5/8	1182'	567	Halliburton		
6-3/4	5-1/2	3753'	300	"		

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Hydrochloric Acid	2000	10-3-36		

Results of shooting or chemical treatment

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from 0 feet to 3870 feet, and from feet to feet

Cable toops were used from feet to feet, and from feet to feet

## PRODUCTION

Put to producing October 16th, 1936

The production of the first 24 hours was 438 barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in

## EMPLOYEES

?, Driller, Driller

, Driller, Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 30th Tulsa, Oklahoma October 30th, 1936

day of October, 1936 Name

Position General Superintendent

Representing Gulf Oil Corporation

Notary Public

Company or Operator

My Commission expires

Address Tulsa, Oklahoma.

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0'	39'		Surface
	318		Sand and red bed
	680		Shale and shells
	855		Red bed and shells
	970		Shale and shells
	1018		Red bed and shells
	1075		Red Rock
	1170		Anhydrite
	1175		Salt
	1555		Salt and potash shells
	1745		Salt
	1920		Salt and shells
	2040		Salt
	2075		Anhydrite and salt
	2280		Salt and anhydrite
	2532		Anhydrite and salt
	2535		Salt and anhydrite and shells
	2579		Anhydrite and lime
	2628		Anhydrite
	2658		Lime
	2879		Anhydrite and Gyp
	2842		Anhydrite
	2895		Anhydrite and lime
	2998		Lime
	3051		Gyp and lime
	3870		Lime