

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Report by Checking Below

|   |  |   |  |   |          |
|---|--|---|--|---|----------|
| REPORT ON BEGINNING DRILLING OPERATIONS |  | REPORT ON RESULT OF TEST OF CASING SHUT-OFF |  | REPORT ON REPAIRING WELL                    |          |
| REPORT ON RESULT OF PLUGGING WELL       |  | REPORT ON RECOMPLETION OPERATION            |  | REPORT ON SQUEEZE (Other) <b>DOC CEMENT</b> | <b>X</b> |

May 6, 1955

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Shell Oil Company

(Company or Operator)

State "E"

(Lease)

J. P. Gibbins

(Contractor)

Well No. 2

in the Lot 10

1/4 of Sec. 6

T. 21-S, R. 36-E, NMPM., Eunice Pool, Lea County.

The Dates of this work were as follows: May 5, 1955

Notice of intention to do the work (~~was~~) (was not) submitted on Form C-102 on....., 19....., (Cross out incorrect words)

and approval of the proposed plan (~~was~~) (was not) obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Squeezed with diesel oil cement to shut off bottom water in State "E" No. 2 as follows:

- (1) Ran retrievable cement retainer on 2 1/2" tubing to 3765'. Pumped 30 barrels oil down casing to push water below tool
- (2) Set tool and loaded casing with oil.
- (3) Pumped 2 barrels diesel oil followed by DOC slurry (50 sacks cement and 9 barrels diesel oil). After injecting 18 barrels flush pressure = 1200 psi. After injecting additional 5 barrels pressure = 4800 psi. Opened tool and reversed out approximately 1/2 barrel cement.

Witnessed by H. B. Brooks  
(Name)

Shell Oil Company  
(Company)

Production Foreman  
(Title)

Approved: *[Signature]*  
OIL CONSERVATION COMMISSION

(Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name D. C. Meyers Original signed by D. C. Meyers

Position Division Mechanical Engineer

Representing Shell Oil Company

Address Box 1957, Hobbs, New Mexico