NEW ""XICO OIL CONSERVATION COM" SSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations

NOTICE OF INTERNATION	TO THOSE CLOSE	0.077770	II .	TORYOT -		
NOTICE OF INTENTION TO TEST CASING SHUT-OFF NOTICE OF INTENTION TO CHANGE PLANS			X	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL		
				OTICE OF OTHERW	INTENTION TO PUVISE ALTER CASIN	ULL OR
NOTICE OF INTENTION	N TO REPAIR W	VELL		NOTICE OF	INTENTION TO PI	LUG WELL
NOTICE OF INTENTION	TO DEEPEN W	VELL		- WA		
		Manage		4		
		Monument,		Place	Jamuary 5,	1936 Date
OIL CONSERVATION anta Fe, New Mexico.						
entlemen:						
following is a notice of	f intentiton to d	lo certain work	as describe	I below at	the	
Company or Operato	m Corporation					in NW 1 NW 1
Sec. 7			, N. M.			_
Lea		_County.	, 14. 141.	P. M.,	2411.00	
5/8" 28# 8thd. the Halliburto sing & Fittings listurbed for t	New Seamles on method. Will be te	ss casing wa	ules and R as set in .200# pum	egulation this we	ell at 2689° i	and cemented
5/8" 28# 8thd. the Halliburto sing & Fittings disturbed for t	New Seamles on method. Will be te	se casing was	ules and R as set in .200# pum	egulation this we	ell at 2689° cure and allowed the cout of courses.	and cemented ad to stand casing and the
-5/8" 28# 8thd. The Halliburto Sing & Fittings disturbed for t	New Seamles on method. Will be te	se casing was	ules and R as set in .200# pum	egulation this we	ell at 2689° i	and cemented ad to stand casing and the
-5/8" 28# 8thd. The Halliburtonsing & Fittings disturbed for tome test applied	New Seamles on method. Will be te	se casing was	ules and R as set in .200# pum	this we pressul be dri	ell at 2689° cure and allowed the cut of cut.	and cemented ed to stand casing and the
the Halliburto sing & Fittings disturbed for t me test applied	New Seamles on method. Will be te	ss casing was sted with 1 es. Cament d to stand	ules and R as set in .200# pum	this we pressul be dri	ell at 2689° cure and allowed the cout of courses.	and cemented ed to stand casing and the
the Halliburto sing & Fittings disturbed for t me test applied	New Seamles on method. Will be te	ss casing was sted with 1 es. Cament d to stand	as set in .200# pumplug wil for thir	this we pressul be drity miunt	ell at 2689° cure and allowed the cut of cut.	and cemented ed to stand casing and the
the Halliburto sing & Fittings disturbed for t me test applied	New Seamles on method. Will be te	ss casing was sted with 1 es. Cament d to stand	as set in 200# pum plug wil for thir	this we pressul be drity miunt	Petroleum Corcompany or	and cemented ed to stand casing and the
-5/8" 28# 8thd. The Halliburto sing & Fittings disturbed for to me test applied oproved cept as follows:	New Seamles on method. Will be tehirty mimut and allowe	ss casing was sted with 1 es. Cament d to stand	as set in 200# pumplug will for thir	this we pressul be drity miunt	Petroleum Cor Company or Laure	and cemented ed to stand casing and the

graph to the Marketine

	et a substitution of the s			
		 en en e		
				٠
			de la companya de la	

and the second s the state of the s

* :			
			$(1-1)^{-1} \cdot (1-1)^{-1}$
	7.9		
	n n		
	115.		

			-
		•	
 *.	n na		

	7 12 2 19	
	2 A 2 2 A	
and the second		