

N. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator GULF OIL CORPORATION	8. Farm or Lease Name Gas Campbell-Houston Com
3. Address of Operator P. O. Box 670, Hobbs, New Mexico 88240	9. Well No. 4
4. Location of Well UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 7 TOWNSHIP 21-S RANGE 36-E NMPM.	10. Field and Pool, or Wildcat Eumont Gas
15. Elevation (Show whether DF, RT, GR, etc.) 3594' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER Abandoning Eunice-Monument; Recomplete ☒
in Eumont Gas

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3624' PB.

9-12-78: Ran 5-1/2" CIBP & set @ 3659'. Capped with 35' of cement, abandoning Eunice-Monument zone. Tested 5-1/2" casing to 500# for 30 minutes; held o.k. Log from 3500' up to 2500'. 9-13-78: Perforated new Eumont intervals with (2) 1/2" JHPF @ 3220', 3277', 3304', 3332', 3402', 3430' & 3461'. 9-14-78: Ran treating equipment. Straddled & acidized each set of new perforations 3220' - 3461' with 250 gallons of 15% NE inhibited iron-stabilized acid. 9-15-78: Swabbed back all acid residue. 9-18-78: Foam frac treated Eumont perforations in 7 stages with 42,000 equivalent gallons containing 43,750# of 20/40 Mesh sand using 90 quality foam, RCNBS & rock salt to divert. Flushed with 750 gallons of 70 quality foam frac pad @ 3850#. ISIP, 3400#. 9/18/78 - 9/25/78: Flowed & swabbed well to clean up. Ran producing equipment.

Well is presently shut-in pending pipe line connections.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED N. P. Sikes, Jr. TITLE Area Engineer DATE 10-26-78

Orig. Signed by
Jerry Sexton
Dist. 1, Supv.

APPROVED BY _____ TITLE _____ DATE OCT 27 1978

CONDITIONS OF APPROVAL, IF ANY: