

1955 OCT 10 PM 3:06

Form C-122

## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Pool Burns Formation Yates County Lea  
Initial        Annual 2 Special        Date of Test 7-25 to 8-1-55  
Company Gulf Oil Corporation Lease Campbell, N Well No. 2  
Unit 2 Sec. 7 Twp. 23 Rge. 36 Purchaser Permian Basin P. Co.  
Casing 5.5 Wt. 27 I.D. 4.092 Set at 3733 Perf. 3050 To 3405  
Tubing 2.375 Wt. 4.7 I.D. 1.975 Set at 3406 Perf.        To         
Gas Pay: From 3050 To 3405 L 3050 xG .600 -GL 2023 Bar. Press. 13.2  
Producing Thru: Casing 2 Tubing        Type Well Single  
Date of Completion: 6-30-51 Packer None Single-Bradenhead-G. G. or G.O. Dual  
Reservoir Temp.       

## OBSERVED DATA

Tested Through (Prover) (Meters) (Meter)Type Taps Pipe

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h <sub>w</sub>	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI										
1.	1	2.75	170.5	10.5	62			92.57		72
2.	1	2.75	170.5	10.5	70			77.2		24
3.	1	2.75	170.5	10.5	66			78.0		24
4.	1	2.75	170.5	10.5	66			65.8		24
5.								77.5		24

## FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpc}}$	Pressure psia	Flow Temp. Factor F <sub>t</sub>	Gravity Factor F <sub>g</sub>	Compress. Factor F <sub>py</sub>	Rate of Flow Q-MCFPD @ 15.025 psia
1.	21.49	77.72	183.7	.9804	.9335	1.023	21.90
2.	21.49	76.12	187.5	.9837	.9335	1.021	20.6
3.	21.49	119.70	184.3	.9843	.9335	1.024	23.85
4.	21.49	136.60	182.7	.9843	.9335	1.025	26.00
5.							

0.02 0.10  
2 3.0%

## PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio        cf/bbl.  
Gravity of Liquid Hydrocarbons 1.025 deg.  
F<sub>c</sub>        (1-e<sup>-S</sup>) 0.129

Specific Gravity Separator Gas         
Specific Gravity Flowing Fluid 0.77  
P<sub>c</sub> 207.5 P<sub>c</sub> 207.5

No.	P <sub>w</sub> P <sub>w</sub> (psia)	P <sub>t</sub> <sup>2</sup>	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup>	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-S</sup> )	P <sub>w</sub> <sup>2</sup>	P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup>	Cal. P <sub>w</sub>	P <sub>w</sub> P <sub>w</sub>
1.	207.5	430.1	2.700	7.29	6.75	430.2	225.5	207.5	66
2.	207.5	430.1	2.463	6.07	5.72	430.2	225.5	207.5	72
3.	207.5	430.1	2.500	6.25	5.83	430.2	225.5	207.5	71
4.	207.5	430.1	2.500	6.25	5.83	430.2	225.5	207.5	68
5.									

Absolute Potential 1270 MCFPD; n 0.70COMPANY Gulf Oil CorporationADDRESS Box 21.67, Dallas, N.M.AGENT and TITLE H. L. Smith

WITNESSED

COMPANY

REMARKS

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

$Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.

$P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia

$P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

$P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

$P_f$  = Meter pressure, psia.

$h_w$  = Differential meter pressure, inches water.

$F_g$  = Gravity correction factor.

$F_t$  = Flowing temperature correction factor.

$F_{pv}$  = Supercompressibility factor.

$n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .