

OIL CONSERVATION DIVISION

P. O. BOX 2038
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Free ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

7. Unit Agreement Name
Eunice Monument South I

8. Farm or Lease Name

9. Well No.
288

10. Field and Pool, or Wildcat
Eunice Monument G/SA

11. Elevation (Show whether DF, RT, GR, etc.)
3607

12. County
Lea

UNIT LETTER C 330 FEET FROM THE North LINE AND 2310 FEET FROM
THE West LINE, SECTION 7 TOWNSHIP 21S RANGE 36E NMPM.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

REFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
IMPROVING ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPER. ☐	PLUG AND ABANDONMENT ☐
LL OR ALTER CASING ☐		CASING TEST AND CEMENT JOBS ☐	
OTHER ☐		OTHER <u>(run liner)</u> , log, perf, acdz ☒	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Work performed 11-20-87 through 12-3-87

POOH w/rods and prod. tbg. Tie into Schlumberger CNL log, perforate w/ 4" guns at 1 SPF, 120° phased, prem charge, 3720-3738, 18 holes. All shots fired. Spot 100 gallons 15% NEFE HCL across perf interval. Acdz w/1500gal 15% NEFE HCL w/add. set at 3899
dropping 27 1.1 SG balls in 1st 1000 gal acid. Swab, run 5 1/2" liner, cmt liner w/50sx
Class C cmt. Displace plug at 1.6 bpm, bump plug w/1000#, plug holding, sting out
of liner, WOC 24 hrs. TIH c/o to liner top 3385', brk circ w/ 55 bbls CKF, set pkr at
3357', load annulus tst to 500psi, ok, PU cmt rtnr, TIH to 3294, tst tbg. to 2000psi,
load csg to 500psi, pmp 75 sx Class C cmt, disp w/ FW, sqzd 1100psi, held ok. Stung
out of CIGR, WOC. GIH tag at 3232', Drlg cmt to 3846, Disp csg w/ CKF, Run CBL & CET, Perf
w/ 4" gun 1 CJPF, phased 180°, f/3782-3790, in Zone 1, set pkr at 3790, spot 100 gal
15% NEFE HCL f/ 3790-3688, Acdz perms w/900 gallons 15% NEFE HCL, Swab.LDWS,
TIH w/ 2 7/8 prod. tbg. to 3832., ND BOP, NU tbg flg. Run rods and prod equip. Load
and test to 600#, ck pmp action, ok. turn over to production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

M. E. Abin TITLE Staff Drilling Engineer DATE Dec. 8, 1987
ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR
TITLES OF APPROVAL, IF ANY:

DEC 15 1987

RECEIVED

DEC 14 1987

OCB
HOBBS OFFICE