

Santa Fe, New Mexico

DEPARTMENT OF THE STATE GEOLOGIST


NOTICE OF INTENTION TO DRILL NEW WELL

Rec'd and Fwd.
6-25-32
T. A. Stanciliff
State Oil & Gas Inspector

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector and approval obtained before drilling begins. If changes in the proposed plan are considered advisable a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval.

Mr. E.H. Wells, State Geologist. Hobbs N. Mex., June 20 1932

Dear Sir: You are hereby notified that it is our intention to commence the drilling of a well to be known as State Well No. 1 in NE 1 of Sec. 8 T. 21 S, R. 36 E, N. M. P. M., Eunice Oil Field Lea County



AREA 640 ACRES

LOCATE WELL CORRECTLY

The well is 1980 feet (X) of North line and 1980 feet (X) of East line of Section 8--21--36

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. 5216

Assignment No. _____

If patented land the owner is _____

Address _____

The lessee is Tidal Oil Company Address Tulsa Okla.

The elevation of the derrick floor above sea level is 3196 feet. We propose to drill well with No. rotary to 7" casing point and drill in with cable tools.

Make of Drill _____

We propose to use the following strings of casing and to land or cement them as indicated.

Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented
<u>15 1/2"</u>	<u>70</u>	<u>Second Hand</u>	<u>300</u>	<u>Cemented</u>
<u>9 5/8 OD</u>	<u>36</u>	<u>New Seamless</u>	<u>2900</u>	<u>"</u>
<u>7 OD</u>	<u>24</u>	<u>"</u>	<u>3900</u>	<u>"</u>

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about _____ feet. Additional information:

Intend to cement 9 5/8" with sufficient cement to protect salt. To set 7" thru big gas above pay horizon and use sufficient cement to permanently shut off this gas if encountered. 15 1/2" surface string to be set thru surface water and cemented to top

Sincerely yours,

Approved June 25, 1932
Except as follows:

Tidal Oil Company
Company or Operator.

By F. Schneider

Position Division Superintendent

Send communication regarding well to

Name F. Schneider

Address Hobbs New Mexico.

State Geologist or Oil and Gas Inspector.

T. A. Stanciliff