

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

LOCATE WELL CORRECTLY

Company Continental Oil Co. Address P.O.Box 66, Hobbs, N.M.
Lessor or Tract A.E. Meyer B-9 Field Eunice State N. Mexico
Well No. 5 Sec. 9 T21S R.36E Meridian N.M.P.M. County Lea
Location 600 ft. [N.] of S. Line and 1930 ft. [E.] of W. Line of Sec. 9 Elevation 3606' (Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed _____

Date 6-8-35

Title Dist. Supt.

The summary on this page is for the condition of the well at above date.

Commenced drilling 4-22, 1935 Finished drilling 6-2-, 1935

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from 3792 to 3803 No. 4, from _____ to _____
No. 2, from 3833 to 3855 No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

| Size casing | Weight per foot | Threads per inch | Make | Amount | Kind of shoe | Cut and pulled from | Perforated | | Purpose |
|-------------|-----------------|------------------|--------|---------|--------------|---|------------|----|---------|
| | | | | | | | From | To | |
| 10-3/4" | 45# | 8 | Smless | 87'3" | T.P. | | | | |
| 7-5/8" | 26.40 | 8 | Smless | 1643'7" | Baker | Cement Guide Shoe | | | |
| 5-1/2" | 17# | 10 | " | 3745'1" | Baker | Cement Guide Shoe & Float Collar | | | |
| 2-1/2" | 6.50 | E.U.S.S. | | 3869' | Tubing | set at 3854. Perforation 3844 to 3854'. | | | |

MUDDING AND CEMENTING RECORD

| Size casing | Where set | Number sacks of cement | Method used | Mud gravity | Amount of mud used |
|-------------|-----------|------------------------|-------------|-------------|--------------------|
| 10-3/4" | 110' | 75 | Halliburton | | |
| 7-5/8" | 1646' | 400 | " | | |
| 5-1/2" | 3743' | 400 | " | | |

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____
Adapters—Material _____ Size _____

SHOOTING RECORD

| Size | Shell used | Explosive used | Quantity | Date | Depth shot | Depth cleaned out |
|------|------------|----------------|----------|------|------------|-------------------|
| | | None | | | | |

TOOLS USED

Rotary tools were used from 0 feet to 3853 feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

DATES

Put to producing 6-2-35, 19____

The production for the first 24 hours was 1700 barrels of fluid of which 100 % was oil; _____ %
Flowing thru casing. Gas, 2 million cu. ft.
emulsion; _____ % water; and _____ % sediment. Gravity, °Bé. _____

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____