


N.



NEW MEXICO STATE LAND OFFICE

SANTA FE, NEW MEXICO

DUPLICATE

DEPARTMENT OF THE STATE GEOLOGIST

WELL RECORD

Mail to State Geologist, Santa Fe, New Mexico, not more than ten days after completion of well. Indicate questionable data by following it with (?). Submit in duplicate.

Company Gypsy Oil Company Address Tulsa, Oklahoma.
Send correspondence to Gypsy Oil Company Address Hobbs, New Mexico.
Bell Ramsey (State) Well No. 1 in SW/4 of Sec. 9, T. 21, R. 36, N. M. P. M., Kunice Oil Field Lee County.
If State land the oil and gas lease is No. 15711 Assignment No. Unknown
If patented land the owner is _____, Address _____
The lessee is Gypsy Oil Company, Address Tulsa, Oklahoma
If not state or patented land, give status _____
Drilling commenced 7/23/34 19____. Drilling was completed 9/12/34 19____
Name of drilling contractor Company Care Drill, Address Tulsa, Oklahoma.
Elevation above sea level at top of casing 3610 Est. feet.
The information given is to be kept confidential until Not Confidential 19____.

OIL SANDS OR ZONES

Top

No. 1, from Anhydrite to 1300' No. 4, from upper San Andres to 3730'
No. 2, from Brown Line to 3010' No. 5, from _____ to _____
No. 3, from Samney to 3440' No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & PULLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10"	45#	8	Seam.	387'	None				Shut off water
7"	24#	10	"	2876'	Halliburton				Protect salt
4-3/4"	16#	11-1/2	"	3740'	"				Oil String

MUDDING AND CEMENTING RECORD

SIZE	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	387'	225	Halliburton		
7"	2876'	300	"		
4-3/4"	3740'	25	"		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters—Material _____ Size _____

SHOOTING RECORD

SIZE	SHELL USED	EXPLOSIVE USED	QUANTITY	DATE	DEPTH SHOT	DEPTH CLEANED OUT

TOOLS USED

Rotary tools were used from 0 feet to 3910' feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing 9-13-34, 19____.
The production of the first 24 hours was 1188 barrels of fluid of which 100 % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be _____
If gas well, cu. ft. per 24 hours 2,150,000 Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____

EMPLOYES

W. F. Ferlin, Driller F. A. Hunefelt, Driller
Talmage Brown, Driller C. F. Pippen, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 30th Name O. C. Cummings
day of October, 1934 Position District Superintendent
John L. McCarty, Representing Gypsy Oil Company
Notary Public. Company or Operator.
My commission expires Feb-1-1935

DUPLICATE

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	392		Sand & Surface Rock
392	428		Red Bed
428	438		Red Shale
438	458		Lime
458	542		Red Shale
542	662		Red Shale & Lime Shells
662	801		Lime & Shells
801	951		Red Bed & Lime
951	957		Lime
957	1108		Red bed & Thin Streaks of Lime
1108	1158		Red Bed
1158	1178		Lime
1178	1208		Lime Hard
1208	1299		Lime & Shale
1299	1362		Lime & Anhydrite
1362	1370		Gypsum
1370	1395		Lime & Anhydrite
1395	1485		Lime - Shale - Salt
1485	1772		Anhydrite & Salt
1772	2240		Shale & Salt
2240	2320		Salt & Anhydrite
2320	2441		Anhydrite & Shale
2441	2471		Lime
2471	2593		Anhydrite & Salt
2593	2670		Lime & Shale
2670	2683		Gypsum
2683	2697		Anhydrite
2697	2723		Lime
2723	2789		Anhydrite
2789	2802		Lime
2802	2806		Anhydrite & Gypsum
2806	2833		Anhydrite & Shale
2833	2887		Anhydrite
2887	2979		Lime
2979	3001		Anhydrite
3001	3009		Lime
3009	3039		Lime Medium Hard
3039	3106		Lime
3106	3131		Lime Medium Hard
3131	3147		Lime
3147	3168		Lime & Anhydrite
3168	3235		Lime
3235	3246		Lime Hard
3246	3387		Lime
3387	3407		Broken Lime
3407	3478		Lime
3478	3494		Sandy Lime
3494	3505		Lime
3505	3511		Lime Wet Streaks of Oil
3511	3532		Lime Little Oil Sand
3532	3557		Lime
3557	3559		Blue Shale
3559	3572		Hard Lime
3572	3581		Lime
3581	3627		Brown Lime
3627	3910		Lime