

OIL AND MINERALS DEPARTMENT	
NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Well ☐ GAS WELL ☐ OTHER: <u>Injector</u>	7. Unit Agreement Name <u>Eunice Monument South Unit</u>
2. Name of Operator <u>Chevron U.S.A. Inc.</u>	8. Farm or Lease Name
3. Address of Operator <u>P.O. Box 670 Hobbs, NM 88240</u>	9. Well No. <u>342</u>
4. Location of Well UNIT LETTER <u>P</u> <u>330</u> <u>South</u> <u>330</u> FEET FROM THE LINE AND FEET FROM	10. Field and Pool, or Whichever <u>Eunice Monument G/SA</u>
5. <u>East</u> LINE, SECTION <u>9</u> TOWNSHIP <u>21S</u> RANGE <u>36E</u> NMPM.	
11. Elevation (Show whether DF, RT, GR, etc.) <u>3575' GL</u>	12. County <u>Lea</u>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
FORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
GRABIRLY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
OR ALTER CASING ☐		CASING TEST AND CEMENT JOBS ☐	
OTHER ☐		OTHER <u>Sidetrack, Deepen, Convert to Injector</u> ☒	

R-7766

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Sidetracked and deepened from 3760' to 4005'. Ran 16 joints 4" 13.4# L80 liner set @ 4005' with top of liner @ 3513'. Cemented with 100 sacks class "C" 1.5% D127, 1/2#/sack celloflake, 1/2#/sack Tuffplug, 1% CACL2. Plug down 7:00 PM 10/25/86. Drilled out cement. Tested liner and lap to 500 psi for 30 minutes (OK). Ran GR/CCL/CNL logs. Perforated 3706' to 3925' (60 holes). Acidized with 5000 gallons 15% NEFE HCL. Equipped for injection. Tested casing and packer to 600 psi for 30 minutes (OK). Work performed 10/12/86 - 10/30/86.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

J. Amille TITLE Drilling Superintendent DATE 11-12-1986

ORIGINAL SIGNED BY JERRY SEXTON

CO BY JERRY SEXTON TITLE _____ DATE NOV 14 1986

CTIONS OF APPROVAL, IF ANY: