

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

AREA 640 ACRES
LOCATE WELL CORRECTLY

WELL RECORD

DUPLICATE

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Skelly Oil Company

A. J. Adkins

Company or Operator

Lease

Well No. 1 in ONE/4, NW/4 of Sec. 10, T. 21S

R. 36E, N. M. P. M., T. 21S, Lea County.

Well is 660 feet south of the North line and 1800 feet west of the East line of Section 10

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is A. J. Adkins, Address Monument, New Mexico

If Government land the permittee is, Address

The Lessee is Skelly Oil Company, Address Box 1650, Tulsa, Okla.

Drilling commenced July 6, 1936, Drilling was completed August 5, 1936

Name of drilling contractor Lee Drilling Company, Address Tulsa, Oklahoma

Elevation above sea level at top of casing 3585 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 2, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13" OD	25.50#	8	LN	225'				
9-5/8"	26#	8	SS	1139'				
7" OD	24#	10	SS	3760'				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15"	15" O D	225'	250	Halliburton		
11"	9-5/8"	1139'	400	Halliburton		
8-1/4"	7" OD	3760'	250	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3887 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing August 8, 1936

The production of the first 24 hours was 491 barrels of fluid of which 100 % was oil; % emulsion; % water; and % sediment. Gravity, Be.

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

McDow, Driller Hines, Driller

Meadows, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this

day of August, 1936

Notary Public.

Hobbs, New Mexico August 10, 1936

Name J. J. Gurneavy

Position District Superintendent

Representing Skelly Oil Company

Address Hobbs, New Mexico

My Commission expires October 24, 1939

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	160	160	Caliche and Sand
160	210	50	Sand
210	290	80	Red Bed and Red Rock
290	465	175	Red Rock
465	725	260	Red Bed and Shells
725	960	235	Red Rock and Shells
960	1175	215	Red Bed
1175	1285	110	Red Rock and Shells
1285	1440	155	Red Rock and anhydrite
1440	2560	1120	Salt and Shells
2560	2670	110	Salt and Anhydrite
2670	2700	30	Anhydrite
2700	2790	90	Anhydrite and Lime
2790	3776	986	Lime
3776	3887	111	Sandy Lime Pay