NEW-MEXICO OIL CONSERVATION COMMUNICATION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL	
-	Cabba Nam Mandaa Tulin 71 1050
	lebbs New Mexico July 31, 1936 Place Date
OIL CONSERVATION COMMISSION,	
santa Fe, New Mexico.	
Gentlemen: Following is a notice of intentiton to do certain work as	described below at the
	.1na Well No. 1 inC NE/4, NW/
of Sec. 10 , T. 21 , R. 36	, N. M. P. M., Eunice Field,
Lea County.	
	at 3760° with 250 sacks of cement.
Cemented 7° OD casing s Will let stand, drill y	
Cemented 7" OD casing s	t 3760° with 250 sacks of cement.
Cemented 7° OD casing s Will let stand, drill p	t 3760° with 250 sacks of cement.
Cemented 7° OD casing s Will let stand, drill p	t 3760° with 250 sacks of cement.
Cemented 7° OD casing s Will let stand, drill p	at 3760° with 250 sacks of cement. Olug, and test for casing shut-off.
Cemented 7° OD casing s Will let stand, drill p	t 3760° with 250 sacks of cement.
Cemented 7° OD casing s Will let stand, drill p	at 3760° with 250 sacks of cement. Olug, and test for casing shut-off.
Cemented 7° OD casing s Will let stand, drill r TD- 3766'	DUPLICATE Skelly Oil Combany
Cemented 7° OD casing s Will let stand, drill r TD- 3766' Approved	Skelly Oil Company Company or Operator
Cemented 7° OD casing s Will let stand, drill r TD- 3766' Approved	Skelly Oil Company Company or Operator By With 250 sacks of cement. Skelly Oil Company Company or Operator
Cemented 7° OD casing s Will let stand, drill y TD- 3766' Approved	Skelly Oil Company Company or Operator By Position Dist. Superintendent
Cemented 7° OD casing s Will let stand, drill y TD- 3766' Approved	Skelly Oil Company Company or Operator By Position Dist. Superintendent Send communications regarding well to
Cemented 7° OD casing s Will let stand, drill r TD- 3766' Approved	Skelly Oil Company Company or Operator By Position Dist. Superintendent Send communications regarding well to Name Skelly Oil Company
Cemented 7 OD casing a Will let stand, drill g TD- 3766 Approved	Skelly Oil Company Company or Operator By Position Dist. Superintendent Send communications regarding well to

and the second second

(x,y,y,z) = (x,y,z) + (y,y,z) + (y,z) + (y

• Section 1 $\mathbf{r}_{\mathbf{r}}$

 $\mathcal{L}_{\mathbf{v}}$. The first section of $\mathcal{L}_{\mathbf{v}}$ is the first section of $\mathcal{L}_{\mathbf{v}}$. The $\mathcal{L}_{\mathbf{v}}$

A second of the s

 $\mathcal{L}_{i} = \{ oldsymbol{c}_{i} \in oldsymbol{c}_{i+1} \}$