

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. D-1115
7. Unit Agreement Name
8. Farm or Lease Name State D. Co. M.
9. Well No. 1
10. Field and Pool, or Wildcat Eumont
12. County Lea

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator CONOCO INC.
3. Address of Operator P. O. Box 460, Hobbs, N.M. 88240
4. Location of Well UNIT LETTER <u>L</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>11</u> TOWNSHIP <u>21S</u> RANGE <u>36E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)

## 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <u>sidetrack out of casing</u> <input checked="" type="checkbox"/>

### SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1708.

This well was TA'd on 11/4/85 due to problems with stuck pipe encountered when drilling out cmt retainers in a liner. This well is to be turned over to Gulf in the Eunice Monument South Unit Waterflood agreement. The procedure to sidetrack out of the casing and bypass the problem area is as follows:

- ① MIRU
- ② Tag top of cmt @ 3729'. Drill out 3750'
- ③ Press. test csg to 500#; sqz if necessary
- ④ start window w/ starter mill
- ⑤ GHT w/ 4 3/4" flat bottom cone buster mill & drill collars; Finish opening window and start sidetrack
- ⑥ GHT w/ 4 3/4" cone bit and sidetrack to 4091'. Verbal APP'L given by Eddie SEAY on 11/20/85.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie W. Seay TITLE Administrative Supervisor DATE 11-20-85  
Oil & Gas Inspector

NOV 25 1985