STATE OF NEW MEXICO EFCY AND MINERALS DEPARTMENT

| 40. 07 COPICS SCCCIVED | T | |
|------------------------|----|-----|
| DISTRIBUTION | | i |
| SANTA FE | 1 | 1 |
| FILE | | i |
| U.\$.0.5. | 7 | |
| LAND OFFICE | T- | i — |
| OPERATOR | | |

| NO. OF COPIES ACCCIVED | OIL CONSERVATION DIVISIO | N.) |
|---|---|---|
| DISTRIBUTION | P. O. BOX 2088 | |
| SANTAFE | | Form C-103 |
| FILE | SANTA FE, NEW MEXICO 87501 | Revised 10-1-7 |
| U.S.Q.S. | | Sa. Indicate Type of Lease |
| LAND OFFICE | | State Fee KX |
| OPERATOR | | |
| | | 5. State Oil & Gas Lease No. |
| SUNDRY | NOTICES AND REPORTS ON WELLS | All Halleston |
| USE "SPPLICATIO | OSALS TO DRILL ON TO DEEPEN ON PLUG BACK TO A DIFFERENT RESEN- ON FOR PERMIT _** (FORM C-101) FOR SUCH PROPOSALS.) | VOIR. () |
| MELL XX GAS WELL | OTHER- | 7. Unit Agreement Name Eunice Monument Sout |
| ame of Operator | | 8. Farm or Lease Name Unit |
| Chevron U.S | A. Inc. | The second prome |
| idress of Operator | | 9. Well No. |
| P.O. Box 6/ | 0, Hobbs, NM 88240 | 1 |
| ocation of Well | | 351 |
| м э | 20 0 | 10. Field and Pool, or Wildcat |
| UNIT LETTER M3 | 30 FEET FROM THE SOUTH LINE AND 330 | Eunice Monument G/SA |
| | | |
| THE West LINE, SECTION | 12 TOWNSHIP 215 RANGE 36E | NMPM. |
| | | |
| | 15. Elevation (Show whether DF, RT, GR, etc.) | 12. County |
| | 3558 | Lea |
| | | |
| Check Ap | ppropriate Box To Indicate Nature of Notice, Rep | port or Other Data |
| NOTICE OF INT | ENTION TO: SUE | SSEQUENT REPORT OF: |
| | | |
| ORM PEMEDIAL WORK | PLUG AND ABAHDON REMEDIAL WORK | |
| ORAFILY ABANDON | | ALTERING CASING |
| OR ALTER CASING | COMMENCE DRILLING OPHS. | PEGG AND ABANDONMENT |
| | CHANGE PLANS CASING TEST AND CEMENT | |
| | other dpn/loc | /acdz XX |
| HER | | |
| | | |
| escribe Proposed or Completed Opera ork) SEE Rut.E 170%. | ations (Clearly state all pertinent details, and give pertinent date | es, including estimated date of starting any proposes |
| , | | , |
| | | |
| Closs out to | 0 3030 Dwill 5/3030 | 5 2010 |
| elean out to | o 3829. Drill f/3829 to new TD c | I 3910. Circ. hole |
| clean. Spot | t 50bbls CKF. Run CNL-GR-CCL & C. | al., RTH w/ 2 3/8 |

prod. tubing (to 3875), and rods. Test to 500psi, OK. Turn over to production. Work performed August 23 through August 24, 1987.

| nereby certify that the information above is true and com | plete to the best of my knowledge and helief. | |
|---|---|-------------------|
| St Elmer f/M.E. ARu | Staff Drilling Engr. | September 3, 1987 |
| Eddie W. Seay Oil & Gas Inspector ITIONS OF APPROVAL, IF ANY: | Y176.E | SFF 8 1987 |