(Formerly 9-331) DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

BUREAU OF LAND MANAGEMENT

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED
HOBBS, NEW MEXICO 88240
OCT 14 11 39 AM '87
CARLSBAD RESOURCE AREA HEADQUARTERS

1. OIL WELL ☐ GAS WELL ☐ OTHER

2. NAME OF OPERATOR: Chevron U.S.A. Inc.

3. ADDRESS OF OPERATOR: P. O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface: 1980' FNL and 660' FWL

5. LEASE DESIGNATION AND SERIAL NO.: [redacted] LC-032099(B)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7. UNIT AGREEMENT NAME: Eunice Monument South Unit

8. FARM OR LEASE NAME:

9. WELL NO.: 389

10. FIELD AND POOL, OR WILDCAT: Eunice Monument G/SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA: Sec.14,T21S,R36E

12. COUNTY OR PARISH: Lea

13. STATE: NM

14. PERMIT NO.:

15. ELEVATIONS (Show whether DF, RT, GR, etc.): 3566

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐	WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐	FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐	SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☐
REPAIR WELL	☐	CHANGE PLANS	☐	(Other) sqz, reperf,acdz			XX
(Other)				(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

POOH w/prod. equip. Set cmt retainer to 3655'. Pump 100sx Cl C and 200sx Cl C mixed and pumped at 14.8 #/gal. Hesitated last 60sx in 15min. increments, left 1/2bbl cmt on top of retainer. WOC 30 hrs. Drill on ret to 3656, circ hole clean, drlg to 3658, dump 1 1/2sx cmt on top of ret at 3658. Tag cmt at 3640. Drlg cmt and ret to 3704. Circ. Drlg cmt 3704-3790, circ clean, drlg cmt to 3875, circ test squeeze to 300psi, ok. Perf 3764-99, 3810-28, 3840-68 (81 holes) 2 1/8" guns 1 JHPF, set pkr at 3270, acdz w/4000 gal 15% NEFE HCL, swab. RIH w/ prod tbg., ND BOP, NU WH. Space out, test pump to 500psi, ok. RD MO PU. Turn over to production.

Work performed 9-23-87 through 10-1-87.

TD: 3950 PB: 3875

18. I hereby certify that the foregoing is true and correct

SIGNED M. E. Akin TITLE Staff Drilling Engineer DATE October 8, 1987

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

NOV 5 1987

SJS

CARLSBAD, NEW MEXICO

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

RECEIVED
DEC 5 1988
OCD
HOBBS OFFICE