

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL (Plug & Abandon)	XX		

Hobbs, New Mexico

October 23, 1939

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corp-Gypsy Prodn.Div. H. C. Collins

Well No. 5 in the

Company or Operator

Lease

SW/4

of Sec. 14

T. 21S

R. 36E

N. M. P. M.,

Eunice

Field,

Lea

County

The dates of this work were as follows: Started Oct 9, 1939, completed Oct 18, 1939

Notice of intention to do the work was ~~was not~~ submitted on Form C-102 on Oct 4, 1939 19
and approval of the proposed plan was ~~was not~~ obtained. (Cross out incorrect words)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

PLUG AND ABANDON WELL. TD 3865'. Cemented bottom of hole with 35 sax cement, from 3865' to 3866' by Halliburton Cementing Process. Mudded to base of salt and placed 5' cement plug, mudded then to top of salt and placed another 5' cement plug. Hole was then filled to top with heavy mud laden fluid and capped with cement. Regulation marker has been installed, which consists of piece of 4" pipe cemented in bottom of cellar and extending 4 feet above surface of ground.

Casing record:

13 3/8" - 36' - Cement 40 sax: Left in hole - 36'
7 5/8" - 1374' - Cement 600 sax: Left in hole - 1374'
5 1/2" - 3696' - Cement 150 sax: Left in hole - 1663'

Witnessed by Glenn Stach Gulf Oil Corporation Field Foreman
Name Company Title

Subscribed and sworn to before me this

23rd day of October, 1939

J. W. Garner

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name *CCC*

Position District Superintendent

Representing Gulf Oil Corp-Gypsy Prodn. Div.
Company or Operator

My Commission expires February 25, 1942

Address Hobbs, New Mexico.

Remarks:

Roy Garbrough
NameOIL & GAS INSPECTOR
Title