

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Encl., Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-025-04648
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name: Eunice Monument South Unit
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		
2. Name of Operator Chevron USA, Inc.	8. Well No. 428	
3. Address of Operator 15 Smith Rd., Midland, Texas 79705	9. Pool name or Wildcat Eunice Monument, Grayburg, SA	
4. Well Location Unit Letter <u>P</u> : <u>660</u> feet from the <u>South</u> line and <u>660</u> feet from the <u>East</u> line Section <u>15</u> Township <u>21-S</u> Range <u>36-E</u> NMPM County <u>Lea</u>		
10. Elevation (Show whether DR, RKB, RT, GR, etc.)		

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐


SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Notify OCD 24 hrs prior to MI & RU.
2. RIH Set 5 1/2" CIBP @ 3610', (Grayburg) Spot 25 Sx plug 3664'-3400' (Queen) WOC Tag.
3. Displace hole w/MLF, 9.5# Brine w/25# Gel P/BBL.
4. Spot 25 Sx plug 2600'-2400' (B-Salt) WOC Tag.
5. Spot 30 Sx plug 1500'-1200' (7 5/8" Shoe, T-Salt) WOC Tag.
6. Fill 5 1/2" Csg w/30 Sx plug 300'-Surf (10 3/4" Shoe, Surf), WOC Tag.
7. Install dry hole marker.

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE G. R. Bledsoe TITLE HES Specialist DATE 6/17/2002
Type or print name G. R. Bledsoe Telephone No. 915.687.7153
(This space for State use)

APPROVED BY
Conditions of approval, if any:

ORIGINAL SIGNED BY
GARY W. WINK
OC FIELD REPRESENTATIVE II/STAFF MANAGER

JUN 18 2002

5
C

PLUGGING & ABANDONMENT WORKSHEET

(3 STRING CSNG)

OPERATOR CHEVRON USA INC.

LEASE NAME EUNICE MONUMENT SOUTH UNIT

WELL # 428

SECT 15 TWN 21-S RNG 36-E

FROM 460 NSL 660 EWL

TD 4008 FORMATION @ TD

PBTD FORMATION @ PBTD Grayburg


	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	10 3/4	245	SURF	Circ.
INTMED 1	7 5/8	1413	SURF	Circ.
INTMED 2				
PROD	5 1/2	3686	SURF	Circ.

	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1	4"	3668	3908		
LINER 2					

	CUT & PULL	TOP - BOTTOM
INTMED 1	PERFS	
INTMED 2	OPENHOLE	3686 - 3854
PROD		

*REQUIRED PLUGS DISTRICT

	PLUG	TYPE PLUG	SACKS CEMENT	DEPTH
RUSTLER (ANHYD)	1	CIBP		3610
YATES	2	QUEEN	25	3400
QUEEN	3	B-SALT	25	2600
GRAYBURG	4	7 5/8 S	30	1500
SAN ANDRES	5	10 3/4 S	30	300
CAPITAN REEF				
DELAWARE				
BELL CANYON				
CHERRY CANYON				
BRUSHY CANYON				
BONE SPRING				
GLORIETA				
BLINBRY				
TUBB				
DRINKARD				
ABO				
WC				
PENN				
STRAWN				
ATOKA				
MORROW				
MISS				
DEVONIAN				



10 3/4
@ 245
TOC SURF

7 5/8
@ 1413
TOC SURF

5 1/2
@ 3686
TOC SURF

TD 4008

MLF

MLF

MLF