

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-04652
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other INJECTOR		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Chevron U.S.A. Inc.		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 1150, Midland, TX 79702		7. Lease Name or Unit Agreement Name: EUNICE MONUMENT SOUTH UNIT
4. Well Location Unit Letter F : 1980 feet from the NORTH line and 1980 feet from the WEST line Section 15 Township 21S Range 36E NMPM County LEA		8. Well No. 386
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3574'		9. Pool name or Wildcat EUNICE MONUMENT; GRAYBURG-SAN ANDRES

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐

OTHER: **CLEANED OUT, ACZD** ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

WASHED THRU OH 3850'-3930'; MADE 2 PASSES, CIRC 2 TIMES BOTTOMS UP. PPD FOAM DOWN BACKSIDE, WHEN FOAM REACHED 3850', STARTED PPG ACID. ACZD 3850'-3930' W/2000 GALS 15% NEPE HCL. SI WELL 30 MIN TO LET ACID SPEND. FLOWED DOWN; JETTED WELL W/N2. RETURNED WELL TO INJECTION.

WORK PERFORMED 11/15/99

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE J. K. Ripley TITLE REGULATORY O.A. DATE 1/27/00

Type or print name J. K. RIPLEY Telephone No. (915)687-7148

(This space for State use)

APPROVED BY _____ TITLE _____ DATE MAR 20 2000

Conditions of approval, if any:

JCS