	State of New Mexico Energy, Minerals and Natural Resources		Form C-10		
<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240	Energy, winicial	s and inatti	iai Kesoufees	WELL API NO.	Revised March 25, 1
District II 1301 W. Grand Avenue, Artesia, NM 88210	OIL CONSER	VATION	DIVISION	30-025-0465	
District III 1000 Rio Brazos Rd., Aztec, NM 87410		ith St. Fra		5. Indicate Type STATE	
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa I	Fe, NM 87	7505	6. State Oi &	
	ES AND REPORTS (W WELL C			
(DO NOT USE THIS FORM FOR PROPOSAL DIFFERENT RESERVOIR. USE "APPLICAT PROPOSALS.)	LS TO DRILL OR TO DE	EPEN OR PLU	JG BACK TO A		r Unit Agreement Na ment South Unit
1. Type of Well: Oil Well Gas Well	Other				
2. Name of Operator Chevron		u		8. Well No.	
3. Address of Operator 15 Smith		X 79705		9. Pool name s	
4. Well Location				Eunice Monum	ent Grayburg S.A.
Unit Letter N : 66	0 feet from the	South	line and 19)80 cost 600	m the West
40					
	Township 2		_{inge} 36-E R. RKB. RT. GR. e	NMPM tc.)	County Lea
11. Check App NOTICE OF INTE	propriate Box to I	ndicate Na		Report or Other SEQUENT RE	
	PLUG AND ABANDO	N 🔲	REMEDIAL WOR		PORT OF: ALTERING CASING
TEMPORARILY ABANDON (CHANGE PLANS		COMMENCE DR	ILLING OPNS.	PLUG AND
	MULTIPLE COMPLETION		CASING TEST A CEMENT JOB	ND	ABANDONMENT
OTHER:			OTHER:		
1. Set 7" CIBP @ 3475' (Gra	Brine w/25# Gel p/	/BBL ·	fr/3475' to 3300'	Tag @ 3278'	
1	perf w/90sx fr/1770 mt 7" X 9 5/8" csg v 7-02 Approved as to pl Liability under bo surface restoration	to 1500' (w/115sx (1 lugging of and is reta n is comp	2 1/2" shoe) Tag the Well Bore. ined until leted.		189101172737 1111 2111 CD 10000 10000 10000 10000 10000 10000
3. Mix & Pump 40sx plug fr/2 4. Perf 4 holes @ 1770' sqz 5. Perf 4 holes @ 360' circ ci 6. Install dry hole marker 8-7	perf w/90sx fr/1770 mt 7" X 9 5/8" csg v 7-02 Approved as to pl Liability under bo surface restoration	to 1500' (w/115sx (1) lugging of and is retant is composite to the	2 1/2" shoe) Tag the Well Bore. ined until leted.	dge and belief.	827282 AZEL
3. Mix & Pump 40sx plug fr/2 4. Perf 4 holes @ 1770' sqz 5. Perf 4 holes @ 360' circ ci 6. Install dry hole marker 8-7 I hereby certify that the information a	perf w/90sx fr/1770 mt 7" X 9 5/8" csg v 7-02 Approved as to pl Liability under to surface restoration bove is true and comp	to 1500' (w/115sx (1) lugging of and is retant is composite to the	2 1/2" shoe) Tag the Well Bore. ined until leted.	dge and belief.	DATE 8-7-02
3. Mix & Pump 40sx plug fr/2 4. Perf 4 holes @ 1770' sqz 5. Perf 4 holes @ 360' circ ci 6. Install dry hole marker 8-7 I hereby certify that the information a	perf w/90sx fr/1770 mt 7" X 9 5/8" csg v 7-02 Approved as to pl Liability under bo surface restoration	to 1500' (w/115sx (1) lugging of and is retant is composite to the	2 1/2" shoe) Tag the Well Bore. ined until leted.	dge and belief.	827282 AZEL
3. Mix & Pump 40sx plug fr/2 4. Perf 4 holes @ 1770' sqz 5. Perf 4 holes @ 360' circ ci 6. Install dry hole marker 8-7 I hereby certify that the information a SIGNATURE Type or print name (This space for State use) APPPROVED BY Conditions of approved frame:	perf w/90sx fr/1770 mt 7" X 9 5/8" csg v 7-02 Approved as to pl Liability under to surface restoration bove is true and comp	to 1500' (w/115sx (1) lugging of and is retant is composite to the	2 1/2" shoe) Tag the Well Bore. ined until leted.	dge and belief.	DATE 8-7-02
3. Mix & Pump 40sx plug fr/2 4. Perf 4 holes @ 1770' sqz 5. Perf 4 holes @ 360' circ ci 6. Install dry hole marker 8-7 I hereby certify that the information a SHUNATURE Type or print name (This space for State use)	perf w/90sx fr/1770 mt 7" X 9 5/8" csg v 7-02 Approved as to pl Liability under to surface restoration BAGLEY BAGLEY	to 1500' (w/115sx (1) lugging of and is retan is composite to the	2 1/2" shoe) Tag the Well Bore. ined until leted. best of my knowled	dge and belief.	DATE 8-7-02
3. Mix & Pump 40sx plug fr/2 4. Perf 4 holes @ 1770' sqz 5. Perf 4 holes @ 360' circ ci 6. Install dry hole marker 8-7 I hereby certify that the information a SIGNATURE Type or print name (This space for State use) APPPROVED BY Conditions of approved framy:	perf w/90sx fr/1770 mt 7" X 9 5/8" csg v 7-02 Approved as to pl Liability under to surface restoration BAGLEY BAGLEY	to 1500' (w/115sx (1) lugging of and is retan is composite to the	2 1/2" shoe) Tag the Well Bore. ined until leted. best of my knowled	dge and belief.	DATE 8-7-02