

N.

NEW MEXICO OIL AND GAS CONSERVATION COMMISSION

Santa Fe, New Mexico
1936

120371

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

GEORGE F. GETTY OIL COMPANY State "N"
Company or Operator Lease
Well No. 1 in NE NE of Sec. 16, T. 21 S
R. 36 E, N. M. P. M., Funice Field, Lea County.
Well is 660 feet south of the North line and 660 feet west of the East line of Section
If State land the oil and gas lease is No. B-1566 Assignment No. None
If patented land the owner is _____ Address _____
If Government land the permittee is _____ Address _____
The Lessee is George F. Getty Oil Company Address Carlsbad, New Mexico
Drilling commenced 11/20/35 19____ Drilling was completed 12/31/35 19____
Name of drilling contractor Two States Drilling Co Address Dallas, Texas
Elevation above sea level at top of casing 3885 feet.
The information given is to be kept confidential until Not Confidential 19____

OIL SANDS OR ZONES

No. 1, from 3785 to 3885 No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
<u>13</u>	<u>50#</u>	<u>8</u>		<u>250'</u>	<u>Larkin</u>			
<u>9-5/8</u>	<u>36#</u>	<u>8</u>		<u>1393'</u>	<u>Baker</u>			
<u>7"</u>	<u>24#</u>	<u>10</u>		<u>3761'</u>	<u>Baker</u>			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
<u>15</u>	<u>13</u>	<u>250</u>	<u>175</u>	<u>Plug</u>		
<u>12</u>	<u>9-5/8</u>	<u>1393</u>	<u>525</u>	<u>Plug</u>		
<u>8-5/8</u>	<u>7</u>	<u>3761</u>	<u>260</u>	<u>Plug</u>		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3885 feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing Tested 12/31/ 19 35
The production of the first One hours was 243 barrels of fluid of which 100 % was oil; 0 % emulsion; 0 % water; and 0 % sediment. Gravity, Be 34
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. 1250 on Casing

EMPLOYEES

Ellis Driller Nichols Driller
Davis Driller Podkins Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 11thday of September, 1936Jessie Douglas

Carlsbad, N. M. January 3, 1936

Name Red R. ManningPosition Superintendent

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	30	30	Caliche
30	80	50	Caliche & sand
80	229	149	Sand
229	250	21	Red beds
250	450	200	Red beds; shale and shells
450	796	346	Red beds & shells
796	1028	232	Red beds & shells
1028	1175	147	Red beds & red rock
1175	1200	25	Red beds & shells
1200	1205	05	Red beds.
1205	1270	65	Red beds & shells
1270	1323	53	Red beds & blue shale
1323	1331	08	Red beds.
1331	1355	24	Red rock
1355	1393	38	Anhydrite
1393	1470	87	Anhydrite
1470	2285	815	Salt & anhydrite.
2285	2585	300	Salt & anhydrite
2585	2609	24	Anhydrite
2609	2673	64	Salt & anhydrite
2673	2867	94	Anhydrite.
2867	2933	66	Anhydrite & lime
2933	2982	49	Lime & anhydrite
2982	3004	22	Lime
3004	3041	37	Sandy lime
3041	3630	591	Lime
3630	3650	20	Lime Show gas
3650	3722	72	Lime
3722	3775	53	Sandy lime
3775	3770		Equals Steel Line Measurement.
3770	3885	115	Lime TOTAL DEPTH