Form (Feb.	<b>-881 a</b> 1961)
<u> </u>	

## (SUBMIT IN TRIPLICATE)

Land Office	Las Cruces
Lease No	032099 (a)
Unit	P

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

X GEOLOG	
SUNDRY NOTICES A	ND REPORTS ON WELLS
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY Subsequent Report of Cag. Repair K NATURE OF REPORT, NOTICE, OR OTHER DATA)
Lockhart A-18 Well No. 1 is located 330 ft. from	March 20
SE/4 Sec. 18 21S (K Sec. and Sec. No.) (Twp.)	y or Subdivision)
The elevation of the derrick floor above sea l	level is3633 ft. KB
BEFORE WORKOVER: TD 3990', Elev 30 3825-3990', Perf OH 3881-3990'. Pm DOR 25, Daily Allow 30 BO. WORK DO W/4 JSPF. Set Drillable Squeeze To Cmt. circulated between 7" & 9-5/8" retainer at 2960'. Drilled out plu retainer at 2960'. Brilled out plus at 2960'.	airse, weights, and lengths of proposed casings; indicate mudding jobs, comentall other important proposed work)  33' KB, Csg Pt 5-3/16" at 3881'. Pay Penrose  32' KB, Csg Pt 5-3/16" at 3881'. Pay Penrose  32' KB, Csg Pt 5-3/16" at 3030'. Perf at 3000'  38E: Set Drillable BP at 3030'. Perf at 3000'  38E: Set Drillable BP at 3030'. Perf at 3000'  38E: Reversed out 20 sx. Drilled out squeeze  38 at 3030'. Ran tbg, rods and pump. AFTER  38 at 3030'. Ran tbg, ro
I understand that this plan of work must receive approx	val in writing by the Geological Survey before operations may be commenced.
Company	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Funice New Mexico	By State of the st
0/2 USGS NNOCC-2 WAM File Pan Am-Hobbs-2; Atl-Ros-2; Stand-	litleDistrict Superior