

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen to plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ P & A well	5. LEASE DESIGNATION AND SERIAL NO. LC-032099(A)
2. NAME OF OPERATOR CONOCO INC.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 460, Hobbs, N.M. 88240	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit N	8. FARM OR LEASE NAME Lockhart A-18
14. PERMIT NO. 330' FSL & 2310' FWL Not available well was plugged in 1963	9. WELL NO. 5
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	10. FIELD AND POOL, OR WILDCAT Eunice (Pineau) + R.B.D. Fumont Yates TRVrs Queen
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 18-215-36E
	12. COUNTY OR PARISH Lea
	13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENTS ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☒ convert to useable wellbore	
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- ① MIRU on 4-1-86, Cut off P & A marker, Weld on Wellhead. Drilled cmt plugs to 3540'.
- ② Drill out cmt from 3540'-3710'. Drill out aluminum from 3840'-45' and drilled cmt from 3845'-3900'.
- ③ Drill cmt to 3935' (TD) and circ. hole clean. Set RBP @ 3790. Test csg to 500 psi, held for 30 min. Test witnessed by Chevron. Rig down on 4-3-86.

ACCEPTED FOR RECORD

gud
APR 14 1986

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED *Kevin L. Vogel*

TITLE Administrative Supervisor

DATE 4-8-86

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

RECEIVED
APR 17 1986
C.C.B.
HOBBS Office