

CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Federal ☐
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☐ GAS WELL ☐ OTHER- ☐

Name of Operator Injector
Chevron U.S.A. Inc.

Address of Operator
P.O. Box 670 Hobbs, NM 88240

Location of Well

UNIT LETTER J, 1980 FEET FROM THE South LINE AND 1980 FEET FROM
THE East LINE, SECTION 18 TOWNSHIP 21S RANGE 36E NMPM.

7. Unit Agreement Name
Eunice Monument S. Uni

8. Farm or Lease Name

9. Well No.
410

10. Field and Pool, or Wildcat
Eunice Monument G/SA

15. Elevation (Show whether DF, RT, GR, etc.)
3635

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

FORM REMEDIAL WORK ☐
PERMANENTLY ABANDON ☐
OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well P&A'd 2-22-88

MIRU, NU BOP, set 4" CIBP at 3855', break circulation w/10# BW, circ. clean and spot 6sx C neat f/3855' to 3730', POOH to 3718', displace csg w/10# salt gel mud. Run 4.34" gauge ring to 3696', set 5 1/2" CIBP at 3575', run bailer and dump 35' (4 1/2sx H neat) cmt on top of CIBP f/3575' to 3540'. Perf w/4" gun 4 JHPF at 1675', 90° phased, GIH w/ cmt rtnr to 1631', pmp 9bbbs 10# BW thru rtnr and establish circulation to surface thru 7 5/8 intermediate csg at 2 BPM, set rtnr at 1631', pmp 250sx Class C neat at 3BPM w/500psi, displace w/3bbbs 10# BW, circ 25sx to surf. Spot 15sx C neat on top of rtnr, 142' f/1631' to 1489'. POOH w/ setting tool, ND BOP GIH to 218', spot 23sx C neat f/218' to surf., break out WH, install dry hole marker. RD MO PU, cut anchors, clean location.

CHANGE NAME AND OWNERSHIP BACK TO CONOCO INC., MEYER A-1 # 14.

Well bore unacceptable for unit - replaced by #410 drilled 1/8/88 & 1/8/88
I hereby certify that the information above is true and complete to the best of my knowledge and belief.

L.H. Emmet Staff Drilling Engr. Feb. 24, 1988

ORIGINAL SIGNED BY JERRY SEXTON

DISTRICT SUPERVISOR

MAR 10 1988

FOR RECORD ONLY

PA posted & changed. dated 8

RECEIVED
FEB 25 1988
OCD
HOBBS OFFICE

RECEIVED
MAR 1 1988
OCD
HOBBS OFFICE