

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease	State <input type="checkbox"/> Federal <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input checked="" type="checkbox"/> Injector	7. Unit Agreement Name Eunice Monument S. Unit
Name of Operator Chevron U.S.A. Inc.	8. Farm or Lease Name
Address of Operator P.O. Box 670 Hobbs, NM 88240	9. Well No. 410
Location of Well UNIT LETTER <u>J</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>18</u> TOWNSHIP <u>21S</u> RANGE <u>36E</u> WMPM.	10. Field and Pool, or Whidcat Eunice Monument G/SA
11. Elevation (Show whether DF, RT, GR, etc.) 3635	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

ORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
FORABLY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

It is proposed to P&A well as follows:

Set CIBP at 3860' and cap with 35' cement.  
Set CIBP at 3580' and cap with 35' cement.  
Perf 5½" at 1675 and circulate cement to surface on 5½ x 7 5/8" annulus (retainer at 1650') sting out retainer, dump cmt to 1525', go up hole to 158' and set 100' plug across 10" csg shoe (50' above and 50' below).  
Set 50' surface plug.  
Entire hole to be displaced with 9.5#/gal abandonment mud.

Pending Federat Approval (attached)

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

L. H. Emery / M. E. Atkins TITLE Staff Drilling Engineer DATE February 10, 1988  
ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR  
TITL DATE  
ITIONS OF APPROVAL, IF ANY:

FEB 11 1988

REC-110  
JUN 11 1968  
FBI - MEMPHIS