



UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TR (DATE)
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

LC-031740-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Eunice Monument South Unit

8. FARM OR LEASE NAME

9. WELL NO.

410

10. FIELD AND POOL, OR WILDCAT

Eunice Monument G/SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

18-T21S-R36E

12. COUNTY OR PARISH 13. STATE

Lea

NM

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ WIW

2. NAME OF OPERATOR

Chevron U.S.A. Inc.

3. ADDRESS OF OPERATOR

P.O. Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

1980' FSL & 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, ST, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.) *

It is proposed to P&A the well:

Set CIBP at 3860' and cap with 35' cement

Set CIBP at 3580' and cap with 35' cement

Perf 5 1/2" at 1675' and circulate cement to surface on 5 1/2 x 7-5/8" annulus

Set 50' surface plug - spot 100' plugs across 7-5/8" & 10" CSG. Shoes.

Entire hole to be displaced with 9.5#/gal abandonment mud

Subject to
Like Approval
by State

NOV 27 11 27 AM '87
CARLSBAD RESOURCE
AREA HEADQUARTERS

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED M. E. Abim

TITLE Staff Drilling Engineer

DATE 11-25-87

(This space for Federal or State use)

APPROVED BY Richard H. Mann

TITLE Assistant Director

DATE 2-5-88

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED
FEB 10 1988
OCCD
HOBBS OFFICE