

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR  
CONTINENTAL OIL COMPANY
3. ADDRESS OF OPERATOR  
Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980'FNL + 1980'FEL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,  
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- |                      |                          |
|----------------------|--------------------------|
| TEST WATER SHUT-OFF  | <input type="checkbox"/> |
| FRACTURE TREAT       | <input type="checkbox"/> |
| SHOOT OR ACIDIZE     | <input type="checkbox"/> |
| REPAIR WELL          | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> |
| MULTIPLE COMPLETE    | <input type="checkbox"/> |
| CHANGE ZONES         | <input type="checkbox"/> |
| ABANDON*             | <input type="checkbox"/> |

- |  |
|--|
|  |
|  |
|  |
|  |
|  |
|  |
|  |

(other) Squeeze & Report ☒

NT REPORT OF  
**RECEIVED**  
MAY 15 1978  
(NOTE  
U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE  
LC-031740 (a)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Meyer A-1
9. WELL NO.  
7
10. FIELD OR WILDCAT NAME  
Eumont Yates 7 Rivers
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 18, T-21S, R-36E
12. COUNTY OR PARISH  
Lea
13. STATE  
nm
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3664' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Rig up 3-9-78 POOH w/2 3/8" tbg. Pressure test csj to 500 psi. Set 5 1/2" cmt retainer @ 3590'. Pumped 75 sk class "C" cmt. Displaced w/13.5 bbls fresh water. Re-perforate @ 3527', 33', 40', 45', 49', 55', 61', 65', w/2 JSPF. WITH w/2 3/8" tbg with PKr set at 3502'. Rig released 3-16-78. Tested 4-21-78 in 24 hrs. it produced 2 BO, 3 BW, 41 mcf G.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm. A. Rutherford TITLE Admin. Supr. DATE 5-12-78

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

**TITLE**

DATE \_\_\_\_\_

ACCEPTED FOR RECORD  
DATE 2-9-78  
MAY 15 1978  
U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

**\*See Instructions on Reverse Side**

USGS (5), NMFU (4). File