Form 9-331 Dec. 1973

Form Approved. Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

IFASE -		

UNITED STATES	5. LEASE			
DEPARTMENT OF THE INTERIOR LC-03/740 (A)				
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
SUNDRY NOTICES AND REPORTS ON WELLS	Unit agreement name			
(Do not use this form for proposals to drill or to deepen or plumperktole full sent reservoir. Use Form 9-331-C for such proposals.)	NMFU			
	8. FARM OR LEASE NAME TO THE STATE OF THE ST			
1. oil gas well other U.S. CEULOU.OAL SU	9. WELL NO. 7			
TOUR HEAT HEAT	12 = 1			
2. NAME OF OPERATOR CONOCO INC.	10. FIELD OR WILDCAT NAME			
3. ADDRESS OF OPERATOR, N.M. 88240	Eunice-Monument (G-SA)			
	11. SEC., T., R., M., OR BLK. AND SÚRVEY OR			
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA - 17 7 2 1 5 4 3 1 5			
below.) AT SURFACE: 1980 FSL & 660 FWL	Sec. 17, 7-21 S, R-36 E 12. COUNTY OR PARISH 13. STATE			
AT TOP PROD. INTERVAL:	LEA NM			
AT TOTAL DEPTH:	14. API NO.			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	1 - 기가 하는 기가 가장 가장 하는 기가 가장 하는 것이 되었다.			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)			
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:				
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	그는 그는 그는 회사를 가는 것이 없는데 그 그 것이다.			
FRACTURE TREAT				
SHOOT OR ACIDIZE				
REPAIR WELL UPULL OR ALTER CASING UPULL OR A	(NOTE: Report results of multiple completion or zone change on Form 9-330.)			
MULTIPLE COMPLETE	그 그 그 그 사이를 가는 사람들이 살아 다른 사람들이 살아 있다.			
CHANGE ZONES				
ABANDON*				
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertinent.)	firectionally drilled, give subsurface focations and nt to this work.)*			
MIRU. COto 3955'. String shoot 3955-3855'.	Setphr 3785. Acidize Grayburg			
Time to to size . They exist sign sees .				
limestone as follows: Pmp 100 bbls 15% HC	L-NE in 2 stages, Divert with			
intestance of	1 1 1 / 200 pale 10 pag bring			
300 lbs. 50% rock salt & 50% Benzoic fla	thes mixed by 200 gais 10 ppg 11 mc.			
Flush of 30661s. 2% KCL Fresh water. Swa	h back load Scale inhibit as			
Flush by 30 8615, 290 KCL Fresh Water.				
follows: Mix 3 drums chemical in 30 6	6/s. TFW. Release pkr. 3785			
GIHW/ SOPMA, SNto 3903'. Place well on production. Test.				
Subsurface Safety Valve: Manu. and Type	Set @ Ft.			
18. I hereby certify that the foregoing is true and correct				
SIGNED Was Administrative Super	visor DATE January 9,1981			
(This space for Federal or State of	fice use)			
APPROVED BY TITLE	DATE			
CONDITIONS OF APPROVAL, IF ANY:	APPROVED			
	The state of the s			

*See Instructions on Reverse Side