

Form C-103  
**DUPLICATE**

**OIL CONSERVATION COMMISSION**  
Santa Fe, New Mexico  
**MISCELLANEOUS REPORTS ON WELLS**

**RECEIVED**  
JUN 10 1947  
**LEGITIMATE**  
**HOBBS OFFICE**

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	<b>X</b>	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

June 9th, 1947

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Tide Water Associated Oil Company O.L. Coleman Well No. 4 in the \_\_\_\_\_  
Company or Operator Lease

NE/4 of Sec. 17, T. 21-S, R. 37-E, N. M. P. M.,  
Lincoln Field, Lea County.

The dates of this work were as follows: May 22nd to May 27th, 1947

Notice of intention to do the work was 1/11/47 submitted on Form C-102 on May 21st, 1947  
and approval of the proposed plan was 1/11/47 obtained. (Cross out incorrect words.)

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

Dowell Spinner survey was run, and thief section was located from 3944' to 3946'.  
5-gallons of plastic was placed in bottom, 3908' and well gravel packed to 3908'.  
80 gallons of plastic was used to bring it up to 3936', formation taking 60 gallons.  
Plastic and gravel was drilled out to 3944'. Well tested 5 gallons of oil and 5 gals  
of water per hour swabbing. Acidized with 1,000 gallons 15% acid. Well made 37 bbls  
oil and 27 bbls water by swabbing. Installing pumping unit to test further.

Witnessed by H.G. Wesberry, Tide Water Associated Oil Company, Foreman  
Name Company Title

Subscribed and sworn before me this 9th

I hereby swear or affirm that the information given above  
is true and correct.

9th day of June, 1947

Name H.G. Wesberry

Position Foreman

Representing Tide Water Associated Oil Company  
Company or Operator

My commission expires 10/24/49

Address Drawer 11, Hobbs, New Mexico

Remarks:

**APPROVED**  
Date JUN 10 1947

Roy Yarbrough  
Name  
Oil & Gas Inspector  
Title