NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Notice of Intention to Change Plans			
	Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper	
OTICE OF INTENTION O PLUG WELL	Notice of Intention to Plug Back	Notice of Intention to Set Liner	
OTICE OF INTENTION O SQUEEZE	Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)	
otice of Intention of Gun Perforate	Notice of Intention (Other)	Notice of Intention (Other)	
IL CONSERVATION COMMISS ANTA FE, NEW MEXICO	Hobbs, New Mexico	March 3,	1954
entlemen:		· /	
Following is a Notice of Intention	on to do certain work as described below at th	e	
	Operator)		
1# sand per gallen fre	he above well with 6,000 galle om 3770 to total depth. Treat bettom of 5 1/2-inch easing.	ment will be pumped down tub	
1# sand per gallen fre with a packer set in b Bewell, Inc. 5 1/2-inch easing set	om 3770 to total depth. Treat bettem of 5 1/2-inch easing.	ment will be pumped down tub	
1# sand per gallen fre with a packer set in b Bewell, Inc. 5 1/2-inch easing set	om 3770 to total depth. Treat bettem of 5 1/2-inch easing.	ment will be pumped down tub	
1# sand per gallen fre with a packer set in b Bewell, Inc. 5 1/2-inch easing set	om 3770 to total depth. Treat bettem of 5 1/2-inch easing.	ment will be pumped down tub	
1# sand per gallen fre with a packer set in b Bewell, Inc. 5 1/2-inch easing set	om 3770 to total depth. Treat bettem of 5 1/2-inch easing.	ment will be pumped down tub	
1/ sand per gallen fre with a packer set in h Bewell, Inc. 5 1/2-inch easing set Total depth: 3925	om 3770 to total depth. Treat bettem of 5 1/2-inch easing. at 3770	ment will be pumped down tub Work will be performed by	ing
1# sand per gallen fre with a packer set in b Bewell, Inc. 5 1/2-inch easing set	om 3770 to total depth. Treat bettem of 5 1/2-inch easing. at 3770	ment will be pumped down tub Work will be performed by	ing
15 sand per gallen fre with a packer set in bewell, Inc. 5 1/2-inch casing set Total depth: 3925	bettem of 5 1/2-inch easing. at 3770 By	ment will be pumped down tub Work will be performed by	ing dent

Address Box 2075, Hobbs, New Mexico