

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

## MISCELLANEOUS REPORTS ON WELLS

1955 JAN 7 AM 10:51

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS	<input checked="" type="checkbox"/>	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

January 5, 1955

Hobbs, New Mexico

Following is a report on the work done and the results obtained under the heading noted above at the

Drilling &amp; Exploration Company, Inc.

State "F"

Carper Drilling Company, Inc.

Well No. 5 in the SE 1/4 SW 1/4 of Sec. 19

T. 21S, R. 36E, NMPM, Summit (oil zone) Pool, Lea County.

The Dates of this work were as follows: December 30, 1954 to January 2, 1955

Notice of intention to do the work (was) (was not) submitted on Form C-101 on December 21, 1954, 19

and approval of the proposed plan (was) (was not) obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Drilling Operations were commenced on the subject well 7:45 P.M. December 30, 1954. Drilled 11-inch hole to 343 feet in Red Bed. Ten joints of 8 5/8-inch casing was run to 340 feet and cemented with 300 sacks regular cement. Cement circulated to surface. Plug down 8:00 A.M. December 31, 1954. Cement failed to set up. Recemented with 200 sacks regular cement with 2% calcium chloride. Plug down 2:00 A.M. January 1, 1955. Pressure tested casing with 600# for 30 minutes. Final pressure 580#. Drilled out plug 2:00 A.M. January 2, 1955 with 7 7/8-inch bit. Found top of cement plug at 322 feet.

Witnessed by J. C. McGain Drilling & Exploration Co., Inc. Engineer

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name D. C. [Signature]

Position Division Production Superintendent

Representing Drilling &amp; Exploration Co., Inc.

Address Box 2075, Hobbs, New Mexico

(Title)

(Date)