

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-77

CO. BY COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
112742

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER-
2. Name of Operator
TEXACO PRODUCING INC
3. Address of Operator
P.O. BOX 728, HOBBS NEW MEXICO 88240
4. Location of Well
UNIT LETTER A 330 FEET FROM THE NORTH LINE AND 330 FEET FROM
THE EAST LINE, SECTION 19 TOWNSHIP 21-S RANGE 36-E NMPM.

7. Unit Agreement Name
8. Farm or Lease Name
STATE A V
9. Well No.
1
10. Field and Pool, or Shallow
CIVIL INDEPENDENT GRADURE-
SALT ANDRES

11. Elevation (Show whether DF, RT, GR, etc.)
3624' G.R.

12. County
LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- ON DECEMBER 5, 1988 MIRD- INSTALL BOP.
- POH W/TBG, OOI SUBMERSIBLE PUMP, MOTOR, AND PROTECTOR.
- RAW 4 1/2" BIT AND CLEANED OUT WELL TO 3824' (LSE SHOE) TOH.
- RAW 7" CEMENT RETAINER ON WIRELINE. SET AT 3700'
- RU AND STUNG INTO RETAINER. PUMPED 200 SX CLASS C CEMENT INTO OPENHOLE SECTION (3500'-4000')
PULLED OUT OF RETAINER AND SPOTED 6 SX PLUG (3700'-3665') ON TOP OF RETAINER. TOH.
- PULLED ON 7" CSG, STRETCH CHART SHOWED CSG STOCK AT 1700'
- 7 1/2" W/TBG TO 2100'. PUMPED 25 SX CLASS C + 2% CaCl₂ CEMENT PLUG FROM 2100'-2065'. POH
- RIG-UP WIRELINE. CUT 7" CSG @ 1436'. PULLED 50 JOBS OF 7" CSG.
- GIH w/ 2 3/8" TCE OPEN-ENDED TO 1486'. SPOTED 50 SX CLASS C + 2% CaCl₂ CEMENT FROM 1486'-1386'.
- TOH. SHOT DOWN. WCOL.
- TIH w/ 2 3/8" TCE. TAGGED CEMENT AT 1375'. TOH. (TOP AT SALT AT 1430')
- PERFORATED 9 5/8" CSG AT 375'. GIH AND ESTABLISHED CIRCULATION. PUMPED 225 SX CLASS C + 2% CaCl₂ CEMENT. CIRCULATED 15 SXS. TOC AT SURFACE.
- CU OFF WELLHEAD AND INSTALLED DRY HOLE MARKER- WELL PQA 12-14-88.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Kepher TITLE AREA SUPERINTENDENT DATE DEC 12 1988

APPROVED BY R. A. Sadler TITLE OIL & GAS INSPECTOR DATE MAR 7 1989

CONDITIONS OF APPROVAL, IF ANY: