

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☐ OTHER ☒ P & A

Name of Operator ARCO Oil & Gas Company
Division of Atlantic Richfield Company

Address of Operator
P. O. Box 1710, Hobbs, New Mexico 88240

Location of Well

UNIT LETTER 0 330 FEET FROM THE South LINE AND 1650 FEET FROM
East LINE, SECTION 19 TOWNSHIP 21S RANGE 36E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name
State 176

9. Well No.
2

10. Field and Pool, or Wildcat
Eumont Yates 7R Qn

15. Elevation (Show whether DF, RT, GR, etc.)
3667' GR

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Rigged up on 1/20/81. Installed BOP. POH w/ comp assy.
- Set cmt retr @ 3860'. Cmt squeezed OH 3880-3975' & csg 3860-3880' w/200 sx Cl C w/2% CaCl₂. Spot 35' cmt on top of retr.
- Run CBL, indicated TOC @ 2740'.
- Perf'd 4 squeeze holes 1980-81'.
- Spot 9# brine gel mud 3800-1900'.
- Set cmt retr @ 1485'. Cmt squeezed perfs 1980-81' w/925 sx Cl C cmt cont'g 4% gel, 10% salt followed by 200 sx Cl C cmt cont'g 2% CaCl₂. Circ 125 sx cmt to pit. Spot 35' cmt on retr. Spot 9# brine gel mud 1450' to 60' from surf. Filled csg from 60' to surf w/ 25 sx Cl C cmt cont'g 2% CaCl₂.
- Installed regulation dry hole marker. Cleaned & levelled location. P & A Eff: 1/24/81. FINAL REPORT.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED George W. Schmidt

TITLE Dist. Drlg. Supt.

DATE 1/28/81

APPROVED BY David C. C. C.

TITLE OIL & GAS INSPECTOR

DATE NOV 22 1983

CONDITIONS OF APPROVAL, IF ANY: