

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

RAPOLIO OIL COMPANY

State FIVE

Company or Operator

Well No.

in

of Sec.

T.

R. 34-3, N. M. P. M.

Field,

County.

Well is 1650 feet south of the North line and 2320 feet west of the East line of Sec. 19

If State land the oil and gas lease is No. 270 Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Address

Drilling commenced Feb. 23rd 1936 Drilling was completed April 5th 1936

Name of drilling contractor Gardner Bros. Address Wichita Falls, Texas

Elevation above sea level at top of casing 3645 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 2, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
10 1/2	70 1/2	8	?	2897	None			
8-5/8	36 1/2	8	?	2984	Comb. float			
7	24 1/2	8	?	3856	do			
2 1/2 Tbg.	6.50	10		3911'				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10 5/8	10 1/2	284'	285	Halliburton	?	
11 1/2	8-5/8	2983'	280	do	?	
8-5/8	7"	3879'	300	do	?	

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Dynall	2000 gal	4/4/36	2875-2945	

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3645 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing April 7th, 1936 19

The production of the first 24 hours was 84 bbls. per hr. 100 barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

G. F. Mann Driller G. H. Kent Driller
W. F. Grantham Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 14

day of April 1936

Hobbs, New Mexico

Place

April 14, 1936.

Date

Name L. Smith

Dist. Supt.

Position

