Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1/1/89

OIL CONSERVATION DIVISION

DISTRICT I P.O. Box 1980, Hobbs, NM 88240				WELL API NO. 30-025-04717			
DISTRICT II P.O. Drawer DD, Artesia, NM 88210				5. Indicate Type of Lease STATE FEE			
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410				State Oil & Gas Lease No.			
SUNDRY NOTICES AND REPORTS ON WELLS							
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)				ease Name or Unit Agreemen	t Name		
	AS OTF	OTHER Re-Enter P&A'd Well			Devonian State		
2. Name of Operator Citation Oil & Gas Corp.				8. Well No. 7			
3. Address of Operator				9. Pool name or Wildcat Eumont Yates Seven Rivers Queen			
8223 Willow Place South, Suite 250, Houston, Texas 77070-5623 4. Well Location				Eumont Pates Seven Rivers Queen			
Unit Letter	: 1980 Feet From The	South	Line and 1980	Feet From The	East Line		
Section 20 Township 21S Range 36E NMPM Lea County							
10. Elevation (Show whether DF, RKB, RT, GR, etc) 3612' (estimated)							
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data							
NOTICE OF INTENTION TO: SUB			SUBSE	SEQUENT REPORT OF:			
PERFORM REMEDIAL WORK	PLUG AND AE	ANDON REN	IEDIAL WORK		ASING		
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING			MENCE DRILLING OPN	IS. PLUG AND A	BANDONMENT		
PULL OR ALTER CASING	L OR ALTER CASING CASING TEST AND CEN			JOB			
OTHER:		ОТН	IER:				
work) SEE RULE 1103. 9/15/97 - drilled hard 3723'; drilled cemen TOC @1825'. Ran 0 3804'- surf; noted 12 cellar & POH. ND V spear, installed 10' o welded on slip-on co POOH with 1760' 5- Tested csg to 500#. I Spotted 250 gals acid @1200#. RU, pump	l cement surface to 56'; t 3723' to 3813' (CIBP). GR/CNL/CCL 3816' - 18 if ill @3816' PB. RIH of the Seg sub. Ran freepoint - 1/2" csg. RIH with nipperf'd Seven Rivers Quel across perfs, acidized wed 4000 gals 4% Kcl with Brady sand, tagged with	85' - 100' and 130' - Circulated hole cles 16'. Tested CIBP to be to 3654', dug out cop of BH, speared 5-indicated csg free @el, welded on 8-5/8": sle, x-0, 44 jts (1768') sen 3324' - 3559' (34 with 1500 gallons 150' for prepad. Frac'd in 0.5/1000# SC-462W	200'. Fell free, FIH an @3813'. Ran GF 600#. Isolated hole fellar to 8' below GI 1/2" csg @BH, split/21775' csg collar, scr 4' casing nipple & 5-1/2" 15.5# K-55 I holes). Dumped 20' NEFE acid with c with 19,723 gals 40'	with bit. Tagged fill - L/CBL/CCL from WLT in csg 355' - 1738'. Ray, installed 8' x 8' spiral cut off old 8-5/8" BH; rewed csg back into csg 8-5/8" x 2000# casing hat C csg; screwed into come on top of CIBP @ lay stabilizer, no diverted linear gel with 60 tons 10/1/97 for build-up.	washed 3606' - D 3816' - 50', an csg insp log culvert for eleased/LD collar @1775'; aead. NU BOP. collar @1775'. 3816' WLM. er. BDF		
TYPE OR PRINT NAME		Debra Harris		TELEPHONE NO	(281) 469-9664		
(This space for State Use) ORIGIN APPROVED BY	IAL SIGNED BY CHRIS I DISTRICT I SUPERVISO	WILLIAMS					